

Model: Power-Xtra - 7S - 25.9V 15A Li-ion BMS Devre - Balans

Stock Code: 900.600.501.160

TECHICAL INFORMATIONS

Item No	Specs / Details		Criteria / Parameters
1	Model	7S - 25.9V 15A Li-ion BMS	7S-15A working current
2	Voltage	Charging voltage	29.4V
3	Current	Maximal continuous charging current	15A
		Maximal continuous discharging current	15A
		Current consumption	≤50μA
4	Overcharge Protection	Over charge detection voltage	4.25V±0.025V
		Over charge detection delay time	0.5~2.0S
		Over charge release voltage	4.05V±0.05V
5	Over Discharge Protection	Over discharge detection voltage	3.00±0.05V
		Over discharge detection delay time	10mS—200mS
		Over discharge release voltage	3.20±0.05V
6	Over Current Protection	Over current detection voltage	0.15±0.025V
		Over current detection current	60±20A
		Detection delay time	5mS—20mS
		Release condition	Cut load or Charging Activation
7	Short Circuit Protection	Detection condition	Exterior shot circuit
		Detection delay time	200~500uS
		Release condition	Cut load or Charging Activation
8	Balance	Balance voltage for single cell	4.2±0.025V
		Balance current for single cell	42±5mA
9	Resistance	Inner resistance	≤20mΩ
10	Temperature	Operating temperature range	-40 ~ +65°C
		Temperature Switch	75°C
		Storage temperature range	-40~ +125°C
11	Dimension	Length	65mm
		Width	40mm
		Thickness	7.5mm

Model: Power-Xtra - 7S - 25.9V 15A Li-ion BMS Devre - Balans

Stock Code: 900.600.501.160

IMAGE / TECHNICAL DRAWING

