



5.1 PACK DÔME FLAX - 5 DÔME FLAX & SUB AIR

Specification sheet

Dôme is a high-end product, Made in France, focusing on miniaturization as much as on high-tech. With its sleek design and lacquered finish, Dôme suits each and every living spaces (on a table, mounted to a wall or an optional stand) and blends in perfectly with a flat screen. Thanks to its Flax cone, sandwich cone made of linen, this 5.1 system gets an important improvement in definition and intelligibility of dialogues as well as a larger spacialization thanks to a better linearity of the frequency response. The system is complemented by the intense and deep sound of Sub Air subwoofer. Wireless, Sub Air sets up without all cables constraints. Its flat innovative design and its high-gloss lacquered "Piano" finish perfectly fit into all kinds of spaces. This high-fidelity Home-Cinema pack will plunge you into the heart of the seventh art works.

Patent N° WO 2014/106713 A1



Key points Dôme Flax

- High-fidelity speaker, patented Flax technology
- Focal sound with advanced technologies
- Integrated speaker: in wall, in ceiling, on furniture or standing
- High-gloss lacquered Aluminium body
- Made in France

Key points Sub Air subwoofer

- Install it wherever you want thanks to the wireless connection (wireless transmitter included)
- High-gloss lacquered "Piano" finish



	Dôme Flax satellite
Type	2-way compact sealed speaker
Drivers	4" (10cm) Flax mid-bass 1" (25mm) Al/Mg inverted dome tweeter
Frequency response (±3dB)	80Hz - 28kHz
Low frequency point (-6dB)	72Hz
Sensitivity (2.83V/1m)	88dB
Nominale impedance	8 Ohms
Minimum impedance	4 Ohms
Crossover frequency	2500Hz
Recommended amplifier power	25 - 100W
Dimensions (HxWxD)	6 ^{3/4} x5 ^{11/16} x5 ^{5/8} " (172x144x143mm)
Net weight	1,9 kg

Type	SUB AIR, Flat bass-reflex subwoofer, integrated 150W BASH® amp
Speaker driver (diameter)	8" (21cm)
Bass cutoff frequency (-6dB)	35Hz
Frequency response (+/- 3dB)	40Hz-200Hz
Crossover cutoff frequency	variable 50 Hz - 200 Hz
Input panel	Left Right / LFE
Continuous power output	110 W
Peak power	150 W
Phase adjustment	0 - 180° switch
Power functions	ON Auto (1 W) OFF (0,5 W)
Dimensions (HxWxD)	16.1"x14.2"x6.3" (410mmx360mmx160mm)
Weight	17 lbs (7,65 Kg)

Type	Wireless connection
Range in Meter	15 meters (in a room)
Sound Sampling	16 bits
Sampling Frequency	44,1kHz
Coding delay (latency)	13ms
Radio transmission powers or sensitivity	0dBm
Radio transmission frequency band	2,4Ghz ISM band