

The ECO Cutting range 81M - 121ECO - 171ECO





For more than 20 years AXXAIR has been developing scalable, flexible and reliable machines featuring our patented concentric clamping design and many other functions.

The frames of our cutting machines 122 - 322 can be fitted with a cutting motor, a bevelling motor or with a TIG welding torch.

Our ECO range differs from this concept and is specialized in cutting thin wall tubes.

It offers the same quality of cut than the CC 122 - 322 range in a more affordable package for customers who do not need to bevel or weld with the same machine.

We developed the ECO cutting range in order to respond to these users looking simply for a cutting solution for thin tubes.

Machines dedicated to thin tubes < 5 mm wall thickness*

Easy to move around and lightweight

Attractive prices

AXXAIR choose Metabo to power our ECO range because of the large speed range and higher torque matching the requirements for cutting stainless steel thin wall tubes.

The handle of the Metabo power unit also makes easy and convenient to rotate the blade around the tube.

Our 121 and 171ECO range share the same safe and efficient diameter setting and blade penetration unit than our CC range.

The ECO range comes in a more affordable package but still features most of the designs that made our more advanced CC rangeso popular among the industry.

Because our ECO range is dedicated to cutting, some of the upgrades and accessories available on the CC range like automatic rotation or automatic clamping are not available for this type of cutting machines.

For more details, accessories and the references please see the following pages of this catalogue.



*depending on the type of steel





81M - 121ECO - 171ECO



No tube deformation

Concentric clamping system



Basic and extra stainless steel jaws: no pollution of stainless steel tubes

Limited vibration and tube distortion

Optimised blade to jaws distance



Cutting precision

Perpendicular cuts < 0.25 mm



Operator safety feature

Penetration check feature

Uptake


121ECO +171ECO: feature a dual blade position allowing to cut elbows or flanges with no wasting of tube.

Motor 1300W

Speed adjustment through gearbox and electronic variator

Cutting capacity:

Up to 5 mm wall thickness*



Easy handling and transportation



*depending on the type of steel

Continuous use

Anti-twist cable with bearings.

Protects the electric cable from damage resulting from rotation around the tube.

Opening capacity						
81M	ø5 - ø78 mm 0.25 – 3 "					
121ECO	ø5 - ø121 mm 0.25 – 4.5 "					
171ECO	ø16 - ø170 mm 0.625 – 6.625 "					







81M - 121ECO - 171ECO

INNOVATIVE ORBITAL SOLUTIONS

Technical features:

With the Metabo power unit, our ECO range features a large range of blade rotation speed and the right torque for cutting stainless steel thin wall tubes.


Electric motor 1300W:

- Mechanical gearbox and electric speed variator
- 50/60 HZ
- single-phase motor

Exept the 81M, all the machines' cutting motors are shipped in a convenient carrying case together with all necessary tools for operating the machine.

Because of it's small form and low weight, the 81M cutting motor and the tools are included in the machine's transport case.







	Product Code	Machine's jaw opening capacity in mm			Dimensions
		With basic jaws	With extra jaws (included)	Net weight	(HxLxw in mm)
120V 1300W	81M11	Ø5 - Ø78	-	15 kg	263 x 346 x 236
	121ECO1	Ø24 - Ø1 <mark>21</mark>	Ø <mark>5</mark> - Ø108	38 kg	432 x 520 x 297
	171ECO1	Ø70 - Ø <mark>170</mark>	Ø <mark>16</mark> - Ø118	44 kg	453 x 550 x 307
230V 1300W	81M21	Ø5 - Ø78	-	15 kg	263 x 346 x 236
	121ECO2	Ø24 - Ø1 <mark>21</mark>	Ø <mark>5</mark> - Ø108	38 kg	432 x 520 x 297
	171ECO2	Ø70 - Ø <mark>170</mark>	Ø <mark>16</mark> - Ø118	44 kg	453 x 550 x 307

