

IB040106 INDUCTIVE SENSORS • INCREASED SWITCHING DISTANCE

sensor inductive, M4x0.5 22long, Flush, Sn: 1, 10-30V DC, PNP NO, IO-Link, Cable 2m PUR (Polyurethane), IP67, Stainless steel 1.4404



MECHANICAL FEATURES

	IV000197
Active area material of sensor	Plastic PET
Ambient temperature	-25 °C 70 °C
Cable length	2 m
Degree of protection (IP)	IP67
Housing design	Cylinder, screw-thread
Housing material	Stainless steel 1.4404
Material of cable sheath	PUR (Polyurethane)
Max. tightening torque	0.8 Nm
Mechanical mounting condition for sensor	Flush
Number of cores	3
Pressure-proof	-
Sensor length	22 mm
Thread length	16 mm
Thread pitch	0.5 mm
Thread size, metric	4
ELECTRICAL FEATURES	
Cascadable	
Correction factor (aluminum)	- 0.5
· · ·	0.6
Correction factor (brass)	0.6
Correction factor (copper)	
Correction factor (St37)	1
Correction factor (stainl. steel)	0.8
Hysteresis	10 %
IO-Link compatible	+
No-load current	10 mA
Norm measuring plate	4x4x1
Rated switching current	100 mA
Relative repeat accuracy	2 %
Reverse polarity protection	+

IPF ELECTRONIC

ELECTRICAL FEATURES

Supply voltage	10 V 30 V
Switching distance	1 mm
Switching frequency	3000 Hz
Type of electrical connection	Cable
Type of switching function	Normally open contact
Type of switching output	PNP
Voltage drop	2 V
Voltage type	DC
With LED display	+
With monitoring function of downstream devices	-
Other	
Packaging dimensions	100mm x 17.0mm x 120mm
Shipping weight	0.03kg


Classification

Tariff code

ipf product group	201
eClass 8.0	27270101
eClass 9.0	27270101
eClass 9.1	27270101
ETIM-5.0	EC002714
ETIM-6.0	EC002714
ETIM-7.0	EC002714


85365019

Connection





Dimensional drawing



Installation



Mounting / installation may only be carried out by a qualified electrician!



Software

Any software, drivers or IODD files that may be required to operate your device can be downloaded free of charge from our homepage: www.ipf-electronic.com

Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality. LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.