

IB081176 INDUCTIVE SENSORS • INCREASED SWITCHING DISTANCE

sensor inductive, M8x1 60long, Flush, Sn: 3, 10-30V DC, NPN NO, Connector M8 3pin, IP67, Nickel silver Chrome-plated



MECHANICAL FEATURES

Active area material of sensor	РВТР
Alignment of cable entry	Axial
Ambient temperature	-25 °C 70 °C
Degree of protection (IP)	IP67
Design	Cylinder, screw-thread
Housing coating	Chrome-plated
Housing material	Nickel silver
Mechanical mounting condition for sensor	Flush
Pressure-proof	-
Sensor length	60 mm
Thread length	45 mm
Thread pitch	1 mm
Thread size, metric	8
ELECTRICAL FEATURES	
Cascadable	
Correction factor (aluminum)	0.3
Correction factor (brass)	0.41
Correction factor (copper)	0.27
Correction factor (St37)	1
Correction factor (stainl. steel)	0.72
Hysteresis	10 %
No-load current	10 mA
Norm measuring plate	9x9x1
Number of pins	3
Rated switching current	200 mA
Relative repeat accuracy	5 %
Reverse polarity protection	+
Short-circuit protection	+
Suitable for safety functions	-
Supply voltage	10 V 30 V
Switching distance	3 mm
Switching frequency	1000 Hz

IPF ELECTRONIC

ELECTRICAL FEATURES

Type of electrical connection	Connector M8
Type of switching function	Normally open contact
Type of switching output	NPN
Voltage drop	2 V
Voltage type	DC
With LED display	+
With monitoring function of downstream devices	-


Other

Packaging dimensions	100mm x 17.0mm x 150mm
Shipping weight	0.02kg
Tariff code	85365019


Classification

ipf product group	201
eClass 8.0	27270101
eClass 9.0	27270101
eClass 9.1	27270101
ETIM-5.0	EC002714
ETIM-6.0	EC002714
ETIM-7.0	EC002714

Connection



Dimensional drawing



Installation



Mounting / installation may only be carried out by a qualified electrician!



Software

Any software, drivers or IODD files that may be required to operate your device can be downloaded free of charge from our



homepage: www.ipf-electronic.com

Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality. LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.