

IB08C851

INDUCTIVE SENSORS • NORM SWITCHING DISTANCE

sensor inductive, M8x1 69long, Flush, Sn: 1, 5-36V DC, Two-wire NC/NO, Connector M12 2pin, IP67, CuZn White bronze



MECHANICAL FEATURES

Active area material of sensor	PBT
Alignment of cable entry	Axial
Ambient temperature	-25 °C ... 80 °C
Degree of protection (IP)	IP67
Design	Cylinder, screw-thread
Housing coating	White bronze
Housing material	CuZn
Mechanical mounting condition for sensor	Flush
Pressure-proof	-
Sensor length	69 mm
Thread length	38 mm
Thread pitch	1 mm
Thread size, metric	8

ELECTRICAL FEATURES

Cascadable	-
Hysteresis	15 %
Min. output current	4 mA
No-load current	0.8 mA
Norm measuring plate	8x8x1
Number of pins	2
Rated switching current	200 mA
Suitable for safety functions	-
Supply voltage	5 V ... 36 V
Switching distance	1 mm
Switching frequency	2700 Hz
Type of electrical connection	Connector M12
Type of switching function	Normally closed contact/normally open contact
Type of switching output	Two-wire
Voltage drop	4.6 V
Voltage type	DC
With LED display	+
With monitoring function of downstream devices	-


Other

Packaging dimensions	100mm x 0.0mm x 120mm
Shipping weight	0.02kg
Tariff code	85365019

Classification

ipf product group	700
eClass 8.0	27270101
eClass 9.0	27270101
eClass 9.1	27270101
ETIM-5.0	EC002714
ETIM-6.0	EC002714
ETIM-7.0	EC002714

Connection



Dimensional drawing

Installation



Mounting / installation may only be carried out by a qualified electrician!

Disposal



Software

Any software, drivers or IOOD files that may be required to operate your device can be downloaded free of charge from our homepage: www.ipf-electronic.com

Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.