

KN340227

CAPACITIVE SENSORS • NORM SWITCHING DISTANCE

Capacitive proximity switches are contact-free sensors. They detect metallic and non-metallic objects, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material, its dimensions and the response sensitivity, which is set via a potentiometer. The vibration-resistant sensors can be approached laterally or frontally. Capacitive proximity switches are used for presence detection (e.g. sealing detection), positioning (e.g. PET bottles), counting (e.g. plastic caps), level detection (e.g. lubricant) or distance measurements (e.g. thickness measurement) of solid and liquid materials.



MECHANICAL FEATURES

Ambient temperature	-25 °C 70 °C
Degree of protection (IP)	IP67
Housing design	Cylinder plain
Housing material	PBT
Mechanical mounting condition for sensor	Non-flush
Pressure-proof	-
Sensor diameter	34 mm
Sensor length	90 mm

ELECTRICAL FEATURES

Max. output current Suitable for safety functions - Switching distance 30 mm Type of electrical connection Connector M12 Type of switching function Normally closed contact Type of switching output Voltage type DC With monitoring function of downstream devices -	Cascadable	-
Switching distance 30 mm Type of electrical connection Connector M12 Type of switching function Normally closed contact Type of switching output PNP Voltage type DC	Max. output current	400 mA
Type of electrical connection Connector M12 Type of switching function Normally closed contact PNP Voltage type DC	Suitable for safety functions	-
Type of switching function Normally closed contact PNP Voltage type DC	Switching distance	30 mm
Type of switching output PNP Voltage type DC	Type of electrical connection	Connector M12
Voltage type DC	Type of switching function	Normally closed contact
	Type of switching output	PNP
With monitoring function of downstream devices -	Voltage type	DC
	With monitoring function of downstream devices	-

OTHER FEATURES

Level detection	+
-----------------	---

Other


Packaging dimensions	76.0mm x 50mm x 121.0mm
Shipping weight	0.16kg
Tariff code	85365019



Classification

ipf product group	243
eClass 8.0	27270102
eClass 9.0	27270102
eClass 9.1	27270102
ETIM-5.0	EC002715
ETIM-6.0	EC002715
ETIM-7.0	EC002715

Connection



Dimensional drawing

Installation



Mounting / installation may only be carried out by a qualified electrician!

Disposal



Software

Please download the software or driver required for operating your new device on our homepage: www.ipf.de

Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.