

SV554800

FLOW SENSORS • SWITCHING AMPLIFIERS

sensor strömung, verstärker 55x75x110 230V AC, Relais, Zeit, Temperatur



MECHANICAL FEATURES

Degree of protection (IP)	IP20
Depth	110 mm
Design	Cuboid
Device design	Built-in device
Height	110 mm
Housing material	Plastic
Length	75 mm
Mounting method	Snap mounting mounting rail
Width	55 mm
ELECTRICAL FEATURES	
Amplifier for flow sensors	+
Flow range for oil	0.03 m/s 3 m/s
Flow range for water	0.01 m/s 1.5 m/s
Galvanic isolation between input and output	
Galvanic isolation between inputs	-
Galvanic isolation between supply voltage and all other current circuits	-
Inherently safe according to EN 60947-5-6 NAMUR	-
Malfunction message output	-
No-load current	34 mA
Number of channels	1
Output circuit, relay change-over contact	2
Power consumption	8 W
Rated supply voltage at AC	230 V 230 V
Rated switching current	4 A
Suitable for safety functions	-
Switching capacity	1000 VA
Switching voltage	250 V
Switching voltage AC	250
Switching voltage DC	60 V
Type of electrical connection	Clamps
Type of switching function	Change-over contact (NO/NC)
Type of voltage supply	Active

IPF ELECTRONIC

ELECTRICAL FEATURES

Voltage type	AC
With LED display	+
OTHER FEATURES	
Operating temperature	-20 °C 60 °C
Other	
Packaging dimensions	74.0mm x 74.0mm x 143.0mm
Shipping weight	0.41kg
Tariff code	85365019

Classification

ipf product group	300
eClass 8.0	27210121
eClass 9.0	27210121
eClass 9.1	27210121
ETIM-5.0	EC001485
ETIM-6.0	EC001485
ETIM-7.0	EC001485

Connection

Dimensional drawing

Installation



Mounting / installation may only be carried out by a qualified electrician!



Software

Any software, drivers or IODD files that may be required to operate your device can be downloaded free of charge from our homepage: www.ipf-electronic.com

Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.