

## YN98C032

### INCLINATION SENSORS • INCLINATION SENSORS

A rotary encoder is a device that converts a rotary motion into a digital output signal, which can be processed on a subsequent evaluation electronics. All of our encoders operate according to the principle of optical scanning. Inside the device there is a pulse disc on which is – depending on the encoder - a unique (absolute) or repetitive (incremental) line graduation, which is scanned by an optical system. The turning of the encoder shaft causes rotation of the pulse disc, which results in a corresponding sampling signal of the optical system. This is finally implemented by an integrated electronics in encoder-specific output signals (e.g. multi-turn, RS422 etc.). For professional installation in many applications, shaft couplings or resilient bases for mounting brackets or flanges are used. In addition, the encoder shaft can be equipped with measuring wheels or pinions in various designs and sizes. Typical applications include the angle measurement on bending machines, length measuring of belt systems or speed measurement on winding systems.



#### MECHANICAL FEATURES

|                         |                          |
|-------------------------|--------------------------|
| Ambient temperature     | -40 °C ... 85 °C         |
| For damp environments   | +                        |
| Inclination angle       | -5 ° ... 5 °             |
| Sensor height           | 75 mm                    |
| Sensor length           | 52.8 mm                  |
| Sensor width            | 22.5 mm                  |
| Version                 | Inclination angle sensor |
| With shaft sealing ring | -                        |

#### ELECTRICAL FEATURES

|                                       |                |
|---------------------------------------|----------------|
| Max. output current                   | 19.9 A         |
| No-load current                       | 35 mA          |
| Reverse polarity protection           | -              |
| Short-circuit protection              | -              |
| Suitable for absolute value detection | -              |
| Supply voltage                        | 9 V ... 30 V   |
| Track A inverted                      | -              |
| Track B inverted                      | -              |
| Type of analog output                 | 4 mA ... 20 mA |
| Voltage type                          | DC             |


#### Other

|                      |                           |
|----------------------|---------------------------|
| Packaging dimensions | 77.0mm x 25.0mm x 123.0mm |
| Shipping weight      | 0.08kg                    |
| Tariff code          | 85365019                  |

## Classification

|                   |          |
|-------------------|----------|
| ipf product group | 700      |
| eClass 8.0        | 27270590 |
| eClass 9.0        | 27270590 |
| eClass 9.1        | 27270590 |
| ETIM-5.0          | EC001486 |
| ETIM-6.0          | EC001486 |
| ETIM-7.0          | EC001486 |

## Connection



## Dimensional drawing

## Installation



Mounting / installation may only be carried out by a qualified electrician!

## Disposal



## Software

Please download the software or driver required for operating your new device on our homepage: [www.ipf.de](http://www.ipf.de)

## Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality. LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.