

System Accessories

Datalogger

KC762/KC761B



Product Features

Smart and flexible

- Support WiFi configuration and baud rate configuration
- Unobstructed communication distance up to 100m

Simple and efficient

- Plug and play, quick installation
- Upgrade the data collector and inverter by cloud platform and APP

Safe and reliable

- Password and encrypted transmission for data protection
- IP65 protection, wide operating temperature range

Technical Specification

Items	KC762	KC761B
Type	Wifi logger	4G logger
Communication Mode		
RS485 communication	Support 4800/9600/115200bps communication distance ≤100m	
WLAN communication	IEEE802.11b/g/n 2.412GHz~2.484GHz	LTE-FDD B1/B3/B5/B7/B8/B20/B28 LTE-TDD B38/B40/B41 GSM 850MHz/900MHz/1800MHz/1900MHz
Power Supply		
DC input voltage	5~15VDC, 1A @15V	
Power consumption	≤5w	
General		
Max. number of devices	10	
Display	LED	
Operating temperature	-30~70°C	
Relative air humidity	0%~100%	
Elevation	≤4000m	
Protection class	IP65	
Dimensions (W×H×D)	48×130.5×31.4mm	
Mounting type	plug and play	
Certification	CE, FCC	CE

- Specification indexes may be subject to changes without further notice.