## **ORION 32700/60 6000mAh** 5C (30A) LiFePO4 Cell



The ORION 32700/60 is a popular LiFePO4 cell. It is intended for use in high capacity, high voltage 32700 battery packs. It can power a wide range of devices including an electric buffer, smart video doorbell, or fiber optic tester.

Do not purchase 32700 batteries before reading and understanding these safety cautions. Using a LiFePO4 cell incorrectly may a cause it to leak, generate heat, smoke, catch on afire, or explode.



## **SAFETY**

- +The cell must stay in the operating temperatures outlined in its data sheet
- +The cell must not exceed voltage, current, and other ratings in its data sheet
- + Store batteries separately, and do not transport without proper packaging
- +Never store or transport together with conductive or metallic objects particularly in a pocket or bag
- +Do not keep in the sun, in a hot car, or anywhere with direct heat
- +If the cell is attached to a PCB, keep it away from high-static environments
- +Recycle discontinued batteries according to local regulations and cover terminals with insulating tape before disposal
- + Discharge end or cut-off voltage in data sheet is lower-limit for discharge cycle and should not be exceeded
- +Charger or device should implement warning for over-voltage, over current, and over-temperature, control of overcharge, and charge timer
- +Be careful not to short-circuit

TECHNICAL DATA	
Cell Dimensions	32.4x70mm
Cell Weight	140 ± 5g
Cell Capacity (nominal/minimum) (1C Rate)	6000mAh
Voltage (nominal)	3.2V
Internal Resistans (23 ± 2°C)	$<8\text{m}\Omega$
Energy Density	19.20Wh
Recommended Standard Charge Method	3000mA, 3.65V CC-CV
Maximum Charge Method	6000mA, 3.65V CC-CV
Maximum Continuous Discharge	18A - 3C
Maximum Peak Discharge	30A - 5C (3s)
Discharge Cut-off Voltage	2.00V
Cycle Life	3000 cycles
Operating Temperature	-20°C to 60°C
Storage Temperature	-20°C to 45°C