## ORION 18650/26 2600mAh 2C BMS (3A) Lithium Ion Cell

The Orion 18650/26 2600 mAh is a popular lithium-ion cell. It is intended for use in high current 18650 battery packs. It can power a wide range of devices including a doorbell, toys or cordless phone.

Do not purchase 18650 batteries before reading and understanding these safety

cautions. Using a lithium-ion cell incorrectly may a cause it to leak, generate heat, smoke, catch on afire, or explode.

## SAFETY

+The cell must stay in the operating temperatures outlined in its data sheet

- + The cell must not exceed voltage, current, and other ratings in its data sheet
- + Store batteries separately, and do not transport without proper packaging

+Never store or transport together with conductive or metallic objects particularly in a pocket or bag

+Do not keep in the sun, in a hot car, or anywhere with direct heat

+If the cell is attached to a PCB, keep it away from high-static environments

+Recycle discontinued batteries according to local regulations and cover terminals with insulating tape before disposal

+ Discharge end or cut-off voltage in data sheet is lower-limit for discharge cycle and should not be exceeded

+ Charger or device should implement warning for over-voltage, over current, and over-temperature, control of overcharge, and charge timer

+Be careful not to short-circuit

## TECHNICAL DATA

| Cell Dimensions                             | 18.5x66mm          |
|---------------------------------------------|--------------------|
| Cell Weight                                 | 49 <b>±</b> 2g     |
| Cell Capacity (nominal/minimum) (0.2C Rate) | 2600mAh            |
| Voltage (nominal)                           | 3.7V               |
| Internal Resistans (23 ± 2°C)               | <100mΩ             |
| Energy Density                              | 9.62 Wh            |
| Recommended Standard Charge Method          | 520mA, 4.2V CC-CV  |
| Maximum Charge Method                       | 2600mA, 4.2V CC-CV |
| Maximum Continuous Discharge                | 3000mA             |
| Discharge Cut-off Voltage                   | 2.75V              |
| Cycle Life                                  | 1000 cycles        |
| Operating Temperature                       | -20°C to 60°C      |
| Storage Temperature                         | -5°C to 35°C       |

info@pilsanelektronik.com www.pilsanelektronik.com Pilsan Plaza, Esenkent Mah. Erzincan Cd. No: 22, 34776 Dudullu Osb/Ümraniye/İstanbul



