



Type: 57668
Designation:..... **Universal Charger**

Systems to charge: **Ni-MH**
Cell sizes:..... AAA, AA,C,D,9V
Cell Configurations:..... AAA, AA, 2 / 4 pcs.
C/D: 2 / 4pcs
9V: 1pcs

| Dimensions: | Charger: | AC/DC-Adapter: |
|--------------------|-----------------|-----------------------|
| Lenght:..... | 166mm | 68mm |
| Widht:..... | 95mm | 29mm |
| Height:..... | 54.8mm | 43mm |
| Weight:..... | 241g | |

| Charging methods: | AC adapter 12V 600mA | Maintenance Charge: |
|--------------------------|-----------------------------|----------------------------|
| AA:..... | Current: 380 mA ± 10% | Current: 0mA |
| AAA:..... | Current: 150 mA ±10% | Current: 0mA |
| C/D | Current:380mA ±10% | Current: 0mA |
| 9V | Current:34mA ±10% | Current: 0mA |

| Housing: | Indications: LED display |
|--------------------------------|--|
| Housing Material:..... ABS V-0 | AAA, AA,cell mix:..... LED solid on = Fast Charge LED off = fully charged or no battery |
| Casing color:..... Black | |

| Protective Functions: | Power: |
|------------------------------|------------------------------------|
| | Primary:..... 100-240 VAC 50/60 Hz |
| | Secondary:..... 2.8V |

Cut off criteria:
Ni-MH standard cells:... Timer:Backup timer 8 hours

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries