



| | | | |
|-------------------|-------------------|---------------------------|----------------------------|
| Type: | 57671 | Systems to charge: | Ni-MH |
| Designation:..... | LCD Multi Charger | Cell sizes:..... | AAA, AA |
| | | Cell Configurations:..... | AAA, AA 2 / 4 / 6 / 8 pcs. |

| Dimensions: | Charger: | AC/DC-Adapter: |
|--------------------|-----------------|-----------------------|
| Lenght:..... | 167 ± 1 mm | 76.4 ± 1 mm |
| Widht:..... | 106 ± 1 mm | 43.2 ± 1 mm |
| Height:..... | 32 ± 1 mm | 30 ± 1 mm |
| Weight:..... | 198 ± 1 g | 111 ± 1 g |

Charging methods: AC adaptor input(200-240V 50Hz) 5.4V 3A:

| | |
|--------------|-----------------------|
| AA:..... | Current: 450mA ± 10% |
| AAA:..... | Current: 200 mA ± 10% |
| 5V USB:..... | Current:1000 mA ± 10% |

Housing:

| | |
|------------------------|-------|
| Housing Material:..... | PA765 |
| Casing color:..... | Black |

Indications: LCD display

| | |
|------------------------|---|
| AAA, AA,cell mix:..... | 1st bar flashing <1.39V |
| AAA, AA,cell mix:..... | 1st bar solid and 2nd bar flashing <1.41V |
| AAA ,AA,cell mix:..... | 1st and 2nd bars solid and 3th bar flashing <1.45V |
| AAA ,AA,cell mix:..... | 1st, 2nd and 3th bars solid and 4th bar flashing <1.54V |
| AAA ,AA,cell mix:..... | All bars are solid : -dv |

Protective Functions:

| | |
|--------------------------|------------------------|
| Reverse protection | Mechanical arrangement |
| Short circuit protection | No current, LCD flash |

Power:

| | |
|-----------------|-------------------|
| Primary:..... | 200-240V AC 50 Hz |
| Secondary:..... | 2.8V |

Cut off criteria:

| | |
|--------------------------|---|
| Ni-MH standard cells:... | Timer: 6.5 hours + / - 1 hour for AA/AAA |
| | -DV: 10mV +/- 2mV / Channel, function immediately |
| | Vmax: >1.65V |

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries