



| | |
|-------------------------------|---------------------------------------|
| Type Designation | 4114 |
| Designation IEC | LR14 |
| System | Zn-MnO ₂ (Alkaline) |
| Shelf Life (Coding)* | 10 years |
| Nominal Voltage [V] | 1.5 |
| Typical Capacity C [mAh] | 7600 (discharge with high-resistance) |
| Permissible Temperature Range | - 10 °C ... 50 °C |
| Weight, approx. [g] | 65,8 |
| Volume [ccm] | 26 |

| | | |
|-----------------|------|------|
| Dimensions [mm] | min: | max: |
| ∅ | 24.9 | 26.2 |
| A | - | 50.0 |
| B | 48.6 | - |
| C | 13.0 | - |
| E | - | 0.9 |
| F | - | 7.5 |
| G | 1.5 | - |

Typical Capacities (at 20°C):



| Discharge Type | Load | End Voltage[V] | 0.9 |
|-------------------|--------|----------------|-------|
| 4M/15M,8H/D,7D/W | 3.9 Ω | Time [h] | 21,7 |
| Portable Lighting | | Capacity [Ah] | 6,32 |
| | | Energy [Wh] | 7,25 |
| Discharge Type | Load | End Voltage[V] | 0.8 |
| 1H/D,7D/W | 3.9 Ω | Time [h] | 24,25 |
| Toy | | Capacity [Ah] | 6,68 |
| | | Energy [Wh] | 7,27 |
| Discharge Type | Load | End Voltage[V] | 0.9 |
| 2H/D,7D/W | 400 mA | Time [h] | 11,3 |
| Portable stereo | | Capacity [Ah] | 4,52 |
| | | Energy [Wh] | 4,94 |

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.