RF500

Handheld Data Terminal / Android



New air medium antenna technology 30% Performance improvement

Handheld Data Terminal









Features •



High Performance Computing Platform

Powerful hardware configurations to ensure applications like massive data collection, 3D real-time display can be operated smoothly.



Android 6.0

Android 6.0 OS, keep optimization and updating



Top Class Materials

CNC aluminum, PC+ABS (SABIC) body with 1.1mm thickness tempered glass offer excellent strength + heat dissipation + electromagnetic shielding features. Soft material around the handle offers a comfortable grip.



Industrial Grade Components

Industrial and military grade components ensure stability and endurance harsh environments.



Ultra Long Operating Time

Pistol style hotswapping battery system makes backup battery more convenient to be restored, so that the operating time is unlimited. (extra batteries are available)



High-end UHF RFID Engine

Equipped with self-developed RFIDbazaar HD5 module based on Impinj R2000 chip, offering the best performance and excellent multi-tag identification ability in the industry.



Outstanding Industrial Design

The idea was inspired by orca, and each single detail has been well refined. The appearance is compact, elegant and balanced, which makes the product eye-catching and impressive.



Excellent Mechanical Protection

Safety drop height 2m/6.56ft. With IP64 protection grade to resist dusts and splashes effectively.



Mechanical parameters

CNC aluminum, PC + PC (SABIC) **Materials**

Dimensions 167*82*129mm

Grip 111*38*47mm

Weight 580a

(standard version including battery)

System Characteristics

Android 6.0 **Operating System**

CPU Quad-core Cortex-A17 / 1.8 GHz

GPU ARM Mali-T764/High performance 3D engine

RAM +ROM 2G+32G

4G+64G Optional V

LCD 5.0 inches/ 1280*720 / IPS / 180°view angle **Touch Screen** 1.1 mm thickness tempered glass/ 10- dot

touch / operable with gloves

Hotswapping Battery Pistol style hotswapping battery system

PSAM*1 / TI TCA 5013 Optional V **PSAM**

Buttons

Power / Volume*2 3 ALPS buttons/ Operating force 2.5N /

Operating life 1,000,000 cycles

3 ALPS buttons/ Operating force 1.6N / **Function Keys**

Operating life 1,000,000 cycles

OMRON button / Operating force 1.27N/ Scan Trigger

Operating life 1,000,000 cycles

6,000mAh chargeable Ii-polymer battery **Power Card Slots** Micro SIM card slot / PSAM card slot*1 **USB Interface** Micro USB / MOLEX connector /Operating

life 10,000 cycles

Audio Large speaker stereo system Button style / 10mm diameter Vibrator

Charge Indicator Bicolor LED

Wireless Communications

WIFI IEEE802.11b / g / n **Bluetooth** Bluetooth 4.0

4G Supported Optional

Application Environment

-20°- +60° **Operating Temp** -30°- +70° **Storage Temp**

Humidity 5%RH - 95%RH (non -condensing)

Protection Grade IP64 **Safety Drop Height** 2 m / 6.56ft

Data Collections

1D Barcode Optional

Engine Motorola EM1350

Support UPC/EA Symbol SE955N/Code128/

Code39/Code93/Code11/

Interleaved 2 of 5/ Discrete 2 of 5/ Chinese 2 of 5/Codabar/MSI/ RSS.etc.

2D Barcode Optional

Engine Zebra SE4750, NLS EM3396, EM3296 Support Data matrix / QR Code / PDF417 /

US Planet / UK Postal, etc.

UHF RFID

RFIDbazaar HD5 **Engine**

Indy R2000 chip

Ø 12*9.5mm / 2300±300Hz Buzzer EPC Global UHF Class 1 Gen 2 / Protocol

ISO 18000-6C / ISO 18000-6B

902-928MHz , 865- 868MHz Optional V Frequency

0~33dBm **Output Power** Peak Inventory Speed > 500 tags /s

UHF Antenna RF500: 4dBi air medium antenna

Read Distance > 10m

Supported Regions US, Canada and other regions following

US FCC

Europe and other regions following ETSI

EN 302 208 China Korea

Malaysia

Camera on

13 megapixels/ automatic focus/ flashlight

Global positioning system

GPS&GLONASS

Accessories









Battery

Desktop charger

Charger and Data cable

Hanging Lace



Handheld Data Terminal



Four color

