

64 CH NVR

16MP/12MP/8MP/6MP/4MP/3MP/1080P/720P HD NVR



SP-3364H8-A3H-B

Produced by **TVT**





SP-3364H8-A3H-B supports 64CH 16MP/12MP /8MP / 6MP / 5MP / 4MP / 3MP / 1080P / 1280 × 1024 / 960P /720P high definition IP video input, which adopts the advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system. This seires supports 64 CH IP input, simultaneous 16 CH playback, and 8K high definition display. So it can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc




Features

- Support 64CH 16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/ D1/CIF IP input
- H.265S/H.265+/H.265/H.264 coding
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timed / motion / sensor/ POS / AI recording
- Playback: 16 CH simultaneous playback
- Search: time slice, time, event, tag, smart and target database search
- Support face detection and comparison
- Support multiple VCA (Video Content Analytics) events, such as region intrusion, tripwire, etc.
- Support OS information overlay on live view and playback
- Support RAID 0, 1, 5, 6, 10
- Express and flexible backup via USB, network and so on
- Preview, record, playback, backup and remote access are supported
- DHCP, DDNS, PPPoE network protocol, etc.
- Compatible with third-party IPCs, such as ONVIF, Hikvision, etc.
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 8K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS

Dimensions



Rear Panel



Specifications

Model		SP-3364H8-A3H-B
System	OS	Embedded Linux
Video	IP Video Input	64
	Network Bandwidth	Incoming: 640Mbps Outgoing: 640Mbps
	Resolution	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/D1/CIF
	Output	HDMI1: 7680×4320@60, 7680×4320@30, 3840×2160@60, 3840×2160@30, 1920×1080, 1280×1024, 1024×768 (When the resolution of HDMI1output is 8K, HDMI2 is unavailable and the maximum resolution of HDMI3 output is 1920×1080) HDMI2: 3840×2160@60, 3840×2160@30, 1920×1080, 1280×1024, 1024×768 HDMI3: 3840×2160@60, 3840×2160@30, 1920×1080, 1280×1024, 1024×768 HDMI4: 1920×1080, 1280×1024, 1024×768 VGA×1: 1920×1080, 1280×1024, 1024×768 (VGA and HDMI1 output the same video source)
	Multi-screen Display	Main output: 1/4/6/8/9/13/16/25/32/36/64 AUX output 1: 1/4/6/8/9/13/16/25/32/36 AUX output2: 1/4/6/8/9/13/16 AUX output 3: 1/4/6/8/9/13/16 Max. 132(64+36+16+16)
	Compression	H.264/H.265/H.265+/H.265S
	Audio	Network input
Local Input		RCA×1 (for two-way talk)
Local Output		RCA×1
HDMI Audio Output		Support
Compression		G.711(U/A)
Record	Resolution	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/D1/CIF
	Frame Rate	N:30fps; P:25fps
Playback	Simultaneous Playback	16CH
	Search	Time slice/time/event/tag/smart search
	Function	Play, pause, FF, Rewind, digital zoom, previous frame, next frame, etc.
Decoding Capability	Live View	1CH 16MP@30 / 4 CH 12MP(only available for main output)
	Playback	1CH 16MP@30 / 4CH 8MP(only available for main output)
Alarm	Mode	Manual, sensor, motion, exception, smart events, etc.
	Input	16CH
	Output	4CH
	Triggering	Record, snapshot, preset, e-mail, etc.
Face	Face Detection Performance (AI by IPC)	64CH
	Face Detection Performance (AI by Device)	4CH(4MP)
	Face Match Performance	16CH
	Comparison Capability	36 pictures/second
	Face Picture Database	32 libraries 10000 face pictures
	Face Picture Search	Search by picture is supported

Specifications

	Database Management	Add, modify, delete and search face pictures
	Face Picture Adding	Add face pictures through APP, WEB and external import
	Face Picture Comparison	Supports successful face recognition alarm and stranger match alarm
	Track	Track display on a map
	Statistical Graph of Information	Bar graph
	Statistical Mode of Information	Statistics by day, week, month, quarter as well as customized time period
Perimeter Protection	Human/Vehicle Classification (AI by IPC)	64CH
	Human/Vehicle Classification (AI by Device)	8CH(2MP)
Video Metadata	Human/Vehicle Attribute Analysis (AI by IPC)	Yes
Other Functions	Fisheye	Supports fisheye dewarping via NVR/Web Client/mobile APP
	Plate Recognition (AI by IPC)	Yes
Network	Protocol	TCP/IP, HTTP, HTTPS, 802.1x, FTP, DHCP, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IPv6, UDP, WebSocket, PPPoE, SNMP, IGMP
	Interface	RJ45 10/100/1000Mbps ×2
	Client Connection	Max. 128 users access
	Network Security	Preview while exiting network security
Mobile Device	OS	iOS, Andriod
Storage	HDD Interface	SATA× 8, max 10TB per HDD
	RAID Type	RAID0,1,5,6,10
	E-SATA Interface	2
Port	USB	USB3.0× 1; USB2.0 × 2(Front:1);
	RS485	Yes (full-duplex), connect to PTZ or keyboard
	Remote Controller	Optional
Others	Power	ATX-200W
	Consumption	≤50W (without HDD)
	Dimensions	445 × 436 × 90mm (W×D×H)
	Certificate	CE,FCC
	Environmental Protection	Directive EU RoHS, WEEE(2012/19/EU), Directive 94/62/EC and REACH(EC1907/2006)
	Working Environment	-10~50°C; Humidity: 10%~90%