# PC4

## Single-Lens People Counting Sensor



## Specifications

|  | PC4 |
|---|---|
| **Basic Parameter** | |
| Image Sensor | 1/4″ progressive scan CMOS |
| Pixels | 5.0 Megapixel |
| Focal Length | 3.15mm |
| Angle of View | Diagonal 160°, Horizontal 120° |
| Installation Height | 2.8m ~ 4.5m |
| **Intelligent Features** | |
| Target Detection | Head and shoulders |
| Target Filter | Shopping cart / Baggage |
| Statistical Method | Counts people entering and exiting separately |
| Detection Region | 1 zone |
| API | CGI, SDK |
| Detection Accuracy | Up to 95%  (Laboratory data) |
| **Network** | |
| Wi-Fi | 802.11 a/b/g/n 2.4G |
| Network Protocols | TCP/IP, UDP, HTTP, DHCP, DNS/DDNS, FTP, IGMP, IPv4 |
| User Interface | Web (IE, Firefox, Chrome) |
| **Interfaces** | |
| Ethernet | 10/100M, RJ45 interface |
| USB | 1 x Micro USB2.0 |
| **Environmental** | |
| Operating Temperature | -30°C ~ 60°C / -22°F ~ 140°F |
| Operating Humidity | 20% ~ 80% |
| **Electrical** | |
| Power | 5V DC ± 10% |
| Power Consumption | Max. 10W |
| **Mechanical** | |
| Weight | 0.15 kg / 0.33lb (Gross Weight) |
| Dimensions | 13.1 × 73 × 3.7mm / 0.52″ x 2.87″ x 0.15″ |

## Features

**Intelligent Functions**
- Support shopping cart and baggage filtering
- Region people counting, two-way Flow detection
- Up to 95% detection accuracy

## Dimensions            Units:mm

KEDACOM |Video Surveillance
Recognitive.Mobile.Integrated