

Low Frequency AC & DC Current Probe

CP2100 Series



- Compact and reliable design
- USB powered, easy to use
- Standard BNC interface



Model \ Spec.	Bandwidth	Current	Range
CP2100A	DC~800KHz	10A/100A	50mA~10Apk(10A) / 1A~100Apk(100A)
CP2100B	DC~2.5MHz	10A/100A	50mA~10Apk(10A) / 1A~100Apk(100A)

Specifications

	CP2100A	CP2100B
Bandwidth	DC~800KHz	DC~2.5MHz
Rise Time	≤437. 5n s	≤140n s
Ranges	10A/100A	
Output sensitivity	0.1V/ (10A) / 0.01V/ (100A)	
DC accuracy (typical)	3%±50mA (10A) 4%±50mA (100A, 500mA~40Apk) 15% (100A, 40Apk~100Apk)	
Measurement range	50mA~10Apk(10A) / 1A~100Apk(100A)	
Max. measuring current	100Apk,70.7Arms(DC+ACpk) / 200Apk-pk,70.7Arms(AC)	
Max. working voltage	CAT III 300V CAT II 600V	
Max. floating voltage	CAT III 300V CAT II 600V	
Max. conductor diameter	13mm	
Output voltage	≤3V	
Overload indication	Buzzer sounds, Button light flashes.	
Power supply	DC 5V	
Probe head size	11*6.1*2.5cm	
Control module size	10.8*5.6*2.6cm	
Length	228cm	
Net Weight	290g	
Packing Weight	1000g	
Packing Size	29.5*23.6*5.7cm	
Working Temperature	0~50°C	
Storage Temperature	-20°C~ 80°C	
Working Humidity	5%~95%(0~40°C, No condensation) / 5%~65%(40°C~ 50°C, No condensation)	
Working Altitude	≤3000m	
Storage Altitude	≤12000m	

* Micsig reserves all the rights of interpretation at any time, it is subject to update without prior notice.

Applications

Motor driver, Inverters, Power Supplies, Avionics ...

Micsig

Shenzhen Micsig Technology Co., Ltd.

Tel: +86-(0)755-88600880 Email: sales@micsig.com Website: www.micsig.com

Address: 1F, Bldg A, Huafeng International Robot Industrial Park, Hangcheng Rd,
Bao'an District, Shenzhen, Guangdong, China, 518126