

➔ Specifications

Parameter	Single Stage	Dual Stage
Center Wavelength (λ_c)	1064 nm	
Bandwidth	± 10 nm	
Peak Isolation	38 dB	55 dB
Isolation in Band (at 23° C)	30 dB	45 dB
Insertion Loss (typical, λ_c , 23° C)	1.5 dB	2.4 dB
Insertion Loss (λ_c , 0-50° C)	2.0 dB	3.4 dB
Return Loss (Input/Output)	55/50 dB	
PDL	0.15 dB	
Maximum Power	300 mW	
Operating Temperature	0° C ~ + 50° C	
Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	5.5 mm (λ) x 35 mm (L)	

Note1: All values specified are without connectors.

Note2: Higher performance specifications upon request.

Note3: Fiber type HI 1060.

➔ Ordering Information

<u>I S</u>	<u>1 0 6 4</u>	<u> </u>	<u> </u>	<u> </u>
Stage Type S: Single Stage D: Dual Stage	Center Wavelength 1060: 1064 nm	Fiber Length A: 1 meter S: Special	Pigtail Style (=Package style) B: bare fiber L: 900 μ m loose tube	Connector 0: None 7: LC/UPC 1: FC/PC 8: LC/SPC 2: FC/APC 9: Special 3: SC/PC A: FC/UPC 4: SC/APC B: SC/UPC 5: FC/SPC C: ST 6: SC/SPC