

➔ Specifications

Parameter	Specification
Center Wavelength	1064 nm
Insertion Loss, 23° C	≤ 1.5 dB (1.3 dB typ.)
Isolation	≥ 22 dB (25 dB typ.)
Return Loss	≥ 45 dB
Cross Talk	≥ 45 dB
Maximum Power (CW)	10 W
PDL	≤ 0.2 dB
Operating Temperature	+ 10° C ~ + 50° C
Storage Temperature	0° C ~ + 60° C
Package Dimensions	80 mm x 42 mm x 41 mm

Note1: All values specified are without connectors. Insertion loss is 0.3 dB higher and return loss is 5 dB lower with connectors.

Note2: Higher performance specifications upon request.

Note3: Fiber type HI 1060 fiber.

Note4: Power handling is 1 W for connectors.

➔ Ordering Information

H P C I R	1 0 6	0 3	A		
	Center Wavelength	Power	Ports	Fiber Length	Pigtail Style
	106: 1064 nm	01: 1 W 02: 2 W 03: 3 W • • • 10: 10 W	03: 3 ports	A: 1 meter	(=Package style) B: bare fiber L: 900 μm loose tube
					Connector
					0: None 7: LC/UPC 1: FC/PC 8: LC/SPC 2: FC/APC 9: Special 3: SC/PC A: FC/UPC 4: SC/APC B: SC/UPC 5: FC/SPC C: ST 6: SC/SPC