

➔ Specifications

Parameter	Specification	
Operating Wavelength Range (Pass Band)	1260-1360 nm or 1460-1620 nm	
Operating Wavelength Range (Reflect Band)	1460-1620 nm or 1260-1360 nm	
Insertion Loss (Pass Band)	0.8 dB	
Insertion Loss (Reflect Band)	0.6 dB	
Isolation (Pass Band)	45 dB	
Isolation (Reflect Band)	15 dB	
Return Loss	50 dB	
Directivity	55 dB	
PDL	0.1 dB	
PMD	0.1 ps	
Maximum Power Handling	300 mW	
Operating Temperature	0° C ~ + 65° C	
Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	Bare Fiber (B)	5.5 mm () x 35 mm (L)
	900 μm loose tube (L)	5.5 mm () x 40 mm (L)
	Heavy Duty (K, R)	100.0 mm x 12.0 mm x 8.0 mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

Note3: Fiber Type – Corning SMF-28e.

➔ Ordering Information

W D M

Wavelength
 13: 1310 nm reflection
 15: 1550 nm reflection

Fiber Length
 A: 1 meter
 B: 1.5 meter
 S: Special

Pigtail Style
 (=Package style)
 B: bare fiber
 L: 900 μm loose tube
 K: 2 mm cable
 R: 3 mm cable

Connector
 0: None 7: LC/UPC
 1: FC/PC 8: LC/SPC
 2: FC/APC 9: Special
 3: SC/PC A: FC/UPC
 4: SC/APC B: SC/UPC
 5: FC/SPC C: ST
 6: SC/SPC