

### ➔ Specifications




Parameter	Premium	A Grade
Operating Wavelength Range	1310 nm / 1550 nm ± 15 nm	
Insertion Loss	0.3 dB	0.5 dB
Isolation	17 dB	15 dB
TDL	0.2 dB	
Return Loss	55 dB	
PDL	0.1 dB	
Operating & Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	Light Duty ( B )	3.0mm ( ) x 60.0mm (L)
	Medium Duty ( L )	3.0mm ( ) x 65.0mm (L)
	Heavy Duty (K, R)	100.0mm x 12.0mm x 8.0mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

Note3: Fiber Type – Corning SMF-28e fiber unless otherwise specified.

### ➔ Ordering Information

<b>W</b>	<b>D</b>	<b>M</b>	<b>2</b>	-		-		-		-		-	
					<b>Port Number</b>		<b>Grade</b>		<b>Fiber Length</b>		<b>Pigtail Style</b>		<b>Connector</b>
					12: 1 x 2 22: 2 x 2		P: Premium A: A Grade		1: 1 meter 2: 2 meter S: Special		(=Package style) B: bare fiber L: 900 μm loose tube K: 2mm cable R: 3mm cable		0: None    7: LC/UPC 1: FC/PC    8: LC/SPC 2: FC/APC    9: Special 3: SC/PC    A: FC/UPC 4: SC/APC    B: SC/UPC 5: FC/SPC    C: ST 6: SC/SPC