



30H PROBE

Magnetic Field Probe: B Field, DC ÷ 1000 Hz

Key Features:

- Frequency range: DC ÷ 1000 Hz
- Dynamic Range: 70 dB
- Directivity: Isotropic
- Sensitivity > 200 μ T
- High pass filter (cut-off @ 1.5Hz).

Compatibility:

- NHT310F and NHT3DL meters

Typical Application:

- Locations where there are patients with pacemakers
- MRI - Magnetic Resonance Imaging
- Galvanic treatments
- Railway Power Supply Plants
- Metalworking processes



Information subject to change without prior notice

MICRORAD

Piazza delle Azalee, 13/14 05018 – Orvieto (TR) - Italy
Tel. +39 0763 393291 /Fax. +39 0763 394423 info@microrad.it - www.microrad.it



30H PROBE

Magnetic Field Probe: B Field, DC ÷ 1000 Hz

Description:

The 30H probe is based on a set of three mutually orthogonal Hall sensors. The three voltages, which correspond to the spatial components of the field, are available individually at the probe output. The NHT310F or NHT3DL meter calculates the resulting isotropic field strength.

The probe detects magnetic fields from 0 to 1000 Hz. It is suitable for use in applications such as Magnetic Resonances Imaging (MRI), materials working plants (galvanic and mills) and power supply plants for railway stations.

The high sensitivity of this probe makes it ideal for exposure measurements in sensitive environments, such as places where people using peacemakers are present.

The presence of a first-order high-pass filter (20 dB / decade) with a 1.5Hz cutting frequency allows to discriminate the static component from the others at higher frequencies. In fact, the filter, when inserted, completely suppresses the continuous component and the probe band becomes 1.5 Hz ÷ 1000 Hz.

TECHNICAL SPECIFICATIONS

Frequency range	0 ÷ 1000 Hz
Type of frequency response	Flat
Measurement range	200 μ T ÷ 600 mT
Dynamic range	70 dB
Sensor type	Hall sensors
Directivity	Isotropic
Frequency response	\pm 0.5 dB (0 Hz ÷ 1 kHz)
Linearity	\pm 0.7 dB (5 ÷ 550 mT)
Isotropic response	\pm 0.5 dB (@ 10 mT)

GENERAL CHARACTERISTICS

Recommended calibration interval	24 months
Operating temperature	-10°C ÷ 50°C
Size	300 x 16 \varnothing (mm)
Weight	63 g
Country of origin	Italy

Information subject to change without prior notice



Piazza delle Azalee, 13/14 05018 – Orvieto (TR) - Italy
 Tel. +39 0763 393291 / Fax. +39 0763 394423 info@microrad.it - www.microrad.it