

➔ Specifications

Parameter	Premium	A Grade
Center Wavelength (c)	1310 nm, 1480 nm, or 1550 nm	
Bandwidth	± 20 nm	
Peak Isolation	56 dB	53 dB
Isolation in Band (± 10 nm, at 23° C)	46 dB	45 dB
Isolation in Band (0-70° C)	35 dB	33 dB
Insertion Loss in Band (0-70° C)	0.6 dB	0.9 dB
Return Loss (Input/Output)	60/55 dB	60/55 dB
PDL (c, 23° C)	0.1 dB	
PMD	0.1 ps	
Maximum Power	500 mW	
Operating Temperature	0° C ~ + 70° C	
Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	5.5 mm () x 35 mm (L)	

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

Note3: Fiber type Corning SMF-28e.

➔ Ordering Information

<u>I</u> <u>S</u> <u>D</u>	-	-	-	-	-	-	-
	T	T	T	T	T	T	T
	Grade	Center Wavelength	Fiber Length	Pigtail Style	(=Package style)	Connector	
	P: Premium	13: 1310 nm	A: 1 meter	B: bare fiber		0: None	7: LC/UPC
	A: A Grade	14: 1480 nm	S: Special	L: 900 μm loose tube		1: FC/PC	8: LC/SPC
		15: 1550 nm				2: FC/APC	9: Special
						3: SC/PC	A: FC/UPC
						4: SC/APC	B: SC/UPC
						5: FC/SPC	C: ST
						6: SC/SPC	