

### ➔ Specifications


Parameter	Premium	A Grade
Operating Wavelength Range	1310 & 1550 nm ± 40 nm	
Insertion Loss (Max)	≤ 7.2 dB	≤ 7.5 dB
Uniformity (Typical)	≤ 1.5 dB	≤ 2.0 dB
Return Loss	≥ 55 dB	≥ 50 dB
Directivity	≥ 55 dB	
PDL	≤ 0.30 dB	≤ 0.35 dB
TDL	≤ 0.2 dB	
Operating & Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	Light Duty ( B )	3.0mm (Φ) x 55.0mm (L)
	Medium Duty ( L )	3.0mm (Φ) x 65.0mm (L)

Note1: All values specified are without connectors.

Note2: Higher performance specifications upon request.

Note3: Fiber Type Corning SMF-28e.

### ➔ Ordering Information

<b>D</b>	<b>W</b>	<b>W</b>	<b>C</b>	-	<b>1</b>	<b>4</b>	-		-		-		-		-		-	
																		
					<b>Port Number</b>			<b>Grade</b>		<b>Coupling Ratio</b>		<b>Fiber Length</b>		<b>Pigtail Style</b>		<b>Connector</b>		
					14: 1 x 4		P: Premium A: A Grade	XY%: XY% EVEN: Equal split		1: 1 meter 2: 2 meter		(=Package style) B: bare fiber L: 900 μm loose tube		0: None 1: FC/PC 2: FC/APC 3: SC/PC 4: SC/APC 5: FC/SPC 6: SC/SPC		7: LC/UPC 8: LC/SPC 9: Special A: FC/UPC B: SC/UPC C: ST		