

➔ Specifications






Parameter	Specification	
Center Wavelength	980 nm & 1550 nm	
Band Width	± 10 nm	
Insertion Loss	0.8 dB	
Isolation	17 dB	
Extinction Ratio	17 dB	
Return Loss	55 dB	
Fiber Type	980 nm port 1550 nm & Common port	SM or 980 PM Panda fiber 980 PM Panda fiber
	Operating & Storage Temperature - 40° C ~ + 85° C	
Package Dimensions	Light Duty (B)	3.0mm () x 60.0mm (L)
	Medium Duty (L)	3.0mm () x 65.0mm (L)
	Heavy Duty (K, R)	100.0mm x 12.0mm x 8.0mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

Note3: Slow axis alignment

➔ Ordering Information

P M W D M 4					
	Port Number 12: 1 x 2 22: 2 x 2	Pump Fiber Type S: SM Fiber P: PM Fiber	Fiber Length 1: 1 meter 2: 2 meter S: Special	Pigtail Style (=Package style) B: bare fiber L: 900 μm loose tube K: 2mm cable R: 3mm cable	Connector 0: None 1: FC/PC 2: FC/APC 3: SC/PC 4: SC/APC 5: FC/SPC 6: SC/SPC 7: LC/UPC 8: LC/SPC 9: Special A: FC/UPC B: SC/UPC C: ST