

➔ Specifications

Parameter	Specification
Center Wavelength (λ_c)	1064 nm
Bandwidth	± 5 nm
Insertion Loss	3.2 dB
Faraday Rotation Angle (single pass)	$45 \pm 3^\circ$
Extinction Ratio (PM)	20 dB
PDL (SM)	0.05 dB
Maximum Power	150 mW
Operating Temperature	$0^\circ\text{C} \sim +50^\circ\text{C}$
Storage Temperature	$-40^\circ\text{C} \sim +85^\circ\text{C}$
Package Dimensions	5.5 mm (ϕ) x 35 mm (L)

Note1: All values specified are without connectors.

Note2: SM fiber type: HI 1060 fiber.

Note3: PM fiber type: PM 980 Panda fiber.

➔ Ordering Information

F R M	-	1 0 6 4	-	A	-	0 1 2 3 4 5 6	-	7 8 9
Fiber Type SM: SM fiber PM: PM fiber		Center Wavelength 1064: 1064 nm		Fiber Length A: 1 meter		Pigtail Style (=Package style) B: bare fiber L: 900 μm loose tube		Connector 0: None 7: LC/UPC 1: FC/PC 8: LC/SPC 2: FC/APC 9: Special 3: SC/PC A: FC/UPC 4: SC/APC B: SC/UPC 5: FC/SPC C: ST 6: SC/SPC