

### ➔ Specifications

Parameter	Specification	
Operating Wavelength Range (Pass Band)	1460-1620 nm	
Operating Wavelength Range (Reflect Band)	1260-1360 nm	
Insertion Loss (Pass Band)	1.0 dB	
Insertion Loss (Reflect Band)	1.0 dB	
Isolation (Pass Band)	45 dB	
Isolation (Reflect Band)	45 dB	
Return Loss	50 dB	
Directivity	55 dB	
PDL	0.15 dB	
PMD	0.1 ps	
Maximum Power Handling	300 mW	
Operating Temperature	0° C ~ + 65° C	
Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	Bare Fiber ( B )	5.5 mm ( ) x 35 mm (L)
	900 μm loose tube ( L )	5.5 mm ( ) x 40 mm (L)
	Heavy Duty (K, R)	100.0 mm x 12.0 mm x 8.0 mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

Note3: Fiber Type – Corning SMF-28e.

Note4: Over operating temperature, all SOP.

### ➔ Ordering Information

<u>W</u> <u>D</u> <u>H</u>	-	<u>1</u> <u>3</u>	-		-		-	
		Wavelength		Fiber Length		Pigtail Style		Connector
		13: 1310 nm reflection		A: 1 meter		(=Package style) B: bare fiber L: 900 μm loose tube K: 2 mm cable R: 3 mm cable		0: None    5: FC/SPC 1: FC/PC    6: SC/SPC 2: FC/APC    7: LC/UPC 3: SC/PC    8: LC/SPC 4: SC/APC    9: Special