

➔ Specifications

Parameter	1 x 4	1x 8	1 x 16	1 x 32	
Operating Wavelength Range	1260-1650 nm				
Insertion Loss	≤ 7.5 dB	≤ 11.0 dB	≤ 14.2 dB	≤ 17.5 dB	
Uniformity	≤ 0.8 dB	≤ 1.0 dB	≤ 1.5 dB	≤ 2.0 dB	
Return Loss	≥ 55 dB				
PDL	≤ 0.2 dB	≤ 0.3 dB	≤ 0.3 dB	≤ 0.4 dB	
Maximum Power	300 mW				
Operating & Storage Temperature	- 40° C ~ + 85° C				
Package Dimensions (in mm)	Pigtailed	40 x 4 x 4	40 x 5 x 4	50 x 5 x 4	55 x 7 x 4
	1RU 19" Rack Mount	438.0 x 330.2 x 43.7			
	LGX Box	159 x 130 x 30	159 x 130 x 59	159 x 130 x 120	152.4 x 130 x 175

Note1: All values specified are without connectors.

Note2: Higher performance specifications are available upon request.

Note3: Fiber Type – Corning SMF-28e.

➔ Ordering Information

P	L	C	-	-	-	-	-	-	-		
											
Port Number				Packaging		Fiber Length		Pigtail Style		Connector	
104: 1 x 4				R: Pigtailed		(for 'R' packaging only)				0: None 7: LC/UPC	
108: 1 x 8				M: 1RU 19" rack mount		1: 1 meter		A: ribbon fiber		1: FC/PC 8: LC/SPC	
116: 1 x 16				X: LGX box		2: 2 meter		B: bare fiber		2: FC/APC 9: Special	
132: 1 x 32								L: 900 μm loose tube		3: SC/ PC A: FC/UPC	
								R: 3mm cable		4: SC/APC B: SC/UPC	
										5: FC/SPC C: ST	
										6: SC/SPC	