

➔ Specifications




Parameter	Specification
Central Wavelength	1310 nm or 1550 nm
Bandwidth	± 20 nm
Insertion Loss	0.8 dB
Isolation	20 dB (40 dB peak isolation)
Extinction Ratio	20 dB
Directivity	50 dB
Return Loss	50 dB
Polarization Alignment	slow axis
Maximum Power	300 mW
PDL	0.2 dB
Operating Temperature	0° C ~ + 70° C
Storage Temperature	- 40° C ~ + 85° C
Package Dimensions	5.5 mm () x 35 mm (L)

Note1: All values specified are without connectors.

Note2: Higher performance specifications upon request.

Note3: Fiber type PM 250 μm Panda fiber.

➔ Ordering Information

P	M	C	I	R	-		-	0	3	-	A	-		-	
						Center Wavelength		Ports		Fiber Length		Pigtail Style		Connector	
						13: 1310 nm 15: 1550 nm		03: 3 ports		A: 1 meter		(=Package style) B: bare fiber L: 900 μm loose tube		0: None 1: FC/PC 2: FC/APC 3: SC/ PC 4: SC/APC 5: FC/SPC 6: SC/SPC	7: LC/UPC 8: LC/SPC 9: Special A: FC/UPC B: SC/UPC C: ST