






➔ Specifications

Parameter	Specification
Center Wavelength (λ_c)	1310, 1480, or 1550 nm
Bandwidth	± 40 nm
Insertion Loss	0.6 dB (0.4 dB typ.)
Extinction Ratio	20 dB (25 dB typ.)
Directivity	50 dB
Return Loss	45 dB
Fiber Type of Port 1 & 2	PM Panda Fiber
Fiber Type of Port 3	SMF 28e or PM Panda Fiber
Maximum Power	300 mW
Fiber Tensile Load	5 N
Operating Temperature	0° C ~ + 70° C
Storage Temperature	- 40° C ~ + 85° C
Package Dimensions	5.5 mm (ϕ) x 35 mm (L)

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

➔ Ordering Information

P B S	-	-	-	-	-	-	-	-
								
Center Wavelength	Fiber Type for Port 3	Fiber Length	Pigtail Style (=Package style)	Connector				
1310: 1310 nm 1480: 1480 nm 1550: 1550 nm	S: SMF-28e fiber P: PM fiber	A: 1 meter	B: bare fiber L: 900 μ m loose tube	0: None 1: FC/PC 2: FC/APC 3: SC/PC 4: SC/APC 5: FC/SPC 6: SC/SPC	7: LC/UPC 8: LC/SPC 9: Special A: FC/UPC B: SC/UPC C: ST			