




➔ Specifications

Parameter	Specification						
Center Wavelength (λ_c)	1310 nm & 1550 nm						
Bandwidth	± 40 nm						
Attenuation Range	1-30 dB						
Attenuation Tolerance	<table border="1"> <tr> <td>1-9 dB</td> <td>± 0.5 dB</td> </tr> <tr> <td>10-14 dB</td> <td>± 1.0 dB</td> </tr> <tr> <td>15-30 dB</td> <td>± 1.5 dB</td> </tr> </table>	1-9 dB	± 0.5 dB	10-14 dB	± 1.0 dB	15-30 dB	± 1.5 dB
1-9 dB	± 0.5 dB						
10-14 dB	± 1.0 dB						
15-30 dB	± 1.5 dB						
Return Loss	<table border="1"> <tr> <td>≥ 50 dB (UPC)</td> </tr> <tr> <td>≥ 60 dB (APC)</td> </tr> </table>	≥ 50 dB (UPC)	≥ 60 dB (APC)				
≥ 50 dB (UPC)							
≥ 60 dB (APC)							
Maximum Power	200 mW						
Attenuator Type	Pluggable (male to female)						
Operating Temperature	- 40° C ~ + 85° C						
Storage Temperature	- 40° C ~ + 85° C						

Note 1: Higher performance specifications available upon request.

Note 2: Default fiber type SMF-28e.

➔ Ordering Information

<u>F</u> <u>A</u>	-	-	-	-	-
					
Attenuation	Connector Type	End Face			
XX: xx dB	SC: SC connector	UPC: UPC polish			
03: 3.0 dB	FC: FC connector	APC: APC polish			
10: 10.0 dB	LC: LC connector				