

TEST-902 TRANSFORMER TEST

TEST-902

Primary Current Injection Test Set

TEST-902 primary current injection test set adopts ARM chip to control the output process and large capacity of toroidal transformer. It is equipped with LCD screen display current meter, also showed primary current value, secondary current value, turn ratio and the action time. Aluminum alloy body with PC panel component the shell. TEST-902 is mainly applied to test CT turn ratio in the power system and the contact resistance etc, which need large current.



Applications

- 1. Primary injection tests
- 2. Protective Relay Testing
- 3. Circuit Breaker Testing
- 4. Current Transformer Testing
- 5. Recloser and Sectionalizers
- 6. Switchgear Testing
- 7. Ground Grid Testing

Features

- 1. Permanent current up to 2000 A, 12KVA
- 2. Max current output up to 2200A
- 3. Built-in digital ammeter 0.5% accuracy
- 4. Built-in digital timer resolution 1 ms (Optional)
- 5. Made up of two units, control and power unit
- 6. Thermal and short-circuit protection

Parameters

Electrical parameters				
Accuracy	±0.5%			
Power Supply (AC)	220V±10%·50A, 50Hz/60Hz or 110V±10%·100A, 50Hz/60Hz			
Current Output (AC)	2000A·6V or 1000A·12V			
Capacity	12KVA			
The current output waveform distortion	≤5%			
Primary current				
Range	0-2200A			
Resolution	0.1A			
Accuracy	<0.5%			



Electrical parameters-continued								
Secondary measurement								
Range	0-6A							
Resolution	0.001A							
Accuracy	<0.5%							
Current duration								
2000A range	2000A 2-3minutes							
	1000A 3-6minutes							
1000A range	1000A 2-3minutes							
With timer(Optional)								
Range	0.0001~999.99S							
Resolution	0.001S							
Accuracy	<0.5% ±5 words							
Mechanical parameters								
Dimensions (W×D×H) (mm)	360×300×295 and 320×300×300							
Weight (kg)	Control Host 35kg,							
	External voltage regulator weight 15kg							
Environmental conditions								
Temperature	-10°C to 40°C							
Relative humidity	≤80%							

Selection Guide

Model	Accuracy	Primary Current	Ammeter (0-6A)	Timer	Power	Injection Current time	Dimension (W×D×H) (mm)	WТ	Remark
TEST-901	0.50%	0-1100A	YES	YES	5KVA	1000A: 2-3min; 500A:3-6min	430×260×260	25KG	Integrated structure
TEST-902	0.50%	0-2200A	YES	OPTIONAL	12KVA	2000A:2-3min; 1000A:3-6min	360×300×295 and 320×300×300	35KG+15KG	Fission structure
TEST-903	0.50%	0-3300A	YES	OPTIONAL	15KVA	3000A: 2-3min; 1500A:3-6min	380×350×360 and 340×290×420	48KG+42KG	Fission structure
TEST-905	0.50%	0-5500A	YES	OPTIONAL	25KVA	5000A:2-3min; 2500A:3-6min	430×430×445 and 550×450×600	68KG+55KG	Fission structure