

➔ Specifications

Parameter		
Operating Wavelength Range		See ordering information
Insertion Loss		≤ 1.0 dB
Isolation		≥ 13 dB
Return Loss		≥ 55 dB
Fiber Type	Pump	SM or PM fiber
	Signal	PM fiber
Extinction Ratio		≥ 55 dB
Operating Temperature		0° C ~ + 70° C
Storage Temperature		- 40° C ~ + 85° C
Package Dimensions	Light Duty (B)	3.0mm (Φ) x 55.0mm (L)
	Medium Duty (L)	3.0mm (Φ) x 60.0mm (L)
	Heavy Duty (K, R)	100.0mm x 12.0mm x 8.0mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications are available upon request.

Note3: Slow axis alignment.

➔ Ordering Information

P	M	W	D	M	S							
						Port Number	Pump Wavelength	Signal Wavelength	Pump Fiber	Fiber Length	Pigtail Style	Connector
						12: 1 x 2	(example)	(example)	Type	1: 1 meter	(=Package style)	0: None 7: LC/UPC
						22: 2 x 2	1550: 1550 nm	2000: 2000 nm	S: SM fiber	2: 2 meter	B: bare fiber	1: FC/PC 8: LC/SPC
						13: 1 x 3			P: PM fiber	S: Special	L: 900 μm loose tube	2: FC/APC 9: Special
						14: 1 x 4					K: 2mm cable	3: SC/PC A: FC/UPC
											R: 3mm cable	4: SC/APC B: SC/UPC
												5: FC/SPC C: ST
												6: SC/SPC