



AVA LED

TN-OF-4

Data Sheet

QUALITY IN DETAIL

OUTDOOR SERIES

TN-OF 4 | TN-OF-4 PRO | TN-OF-4 PLUS



02-03	○ Series and Features
04-05	○ Product Details
06 - 07	○ Product Size - Photo
08-09	○ Cabinet Detail - Safety
10-11	○ Installation Guides
12-13	○ Accessories - Company Info

FEATURES

- Advanced Contrast Brightness Black technology,
- Advanced High Refresh Rate,
- Fast installation of panel to Light Frame,
- Just Signal person to install/uninstall, saving labor cost
- Die-Casting Aluminum-Magnesium frame design, fanless design.
- No noise, lower power consumption, good heat dissipation.

TN-OF-4

- Standart Refresh Rate: 1920Hz
- A Class Led Chip
- Standart PCB Quality
- High Quality MASK

TN-OF-4 PRO

- High Refresh Rate: 3840Hz
- A Class Led Chip
- High Quality PCB
- High Quality MASK



Features

- *** Back Services
- *** Light Weight
- *** Magnesium Die-Casting
- *** 4 in 1 Case weight with products: 129kg.
- *** Faster Cooling
- *** Advanced and safety Lock
- *** Nova Star Controller
- *** Black Shell

○ TECHNICAL SPECIFICATION

PRODUCT DETAILS

MODEL NAME	TN-OF 4	TN-OF 4 PRO
Features		
Series	Standart	Pro
Panel installation type	Fix Instalation	Fix Instalation
Operating Environment	Outdoor	Outdoor
Pixel Pitch	4mm	4mm
Brightness	>5800 Nits	>5800 Nits
Refresh Rate	>1920Hz	>3840Hz
Weight / m2	27,5	27,5
Material Brands		
Lamp	Class A	Class A
Entegred	Chipone	Chipone
Powersupply	Meanwell	Meanwell
Controller	Novastar	Novastar
Connectors : Seetronic	Seetronic	Seetronic
Module Specifications		
Pixel Configuration	SMD 1921	SMD 1921
LED Chip	Cooper	Cooper
LED	Black Shell	Black Shell
Module Size (mm)	320x160	320x160
Module Resolution	80 x 40	80 x 40
Processing	>14-16 Bit	>14-16 Bit
PCB Quality	High Quality	Best Quality
Module - Mask Quality	High Quality	Best Quality
Picture / Video Quality	Standart	High Quality
Grey Scale	>65536	>65536
Cabinet Specifications		
Module Per Cabinet	18 MODULE	18 MODULE
Cabinet Size (mm)	960 x 960 x 105	960 x 960 x 105
Cabinet Material	Die-Casting Magnesium	Die-Casting Magnesium
Weight Per Panel Net kg.	25	25
Cabinet Resolution	240 x 240	240 x 240
Pixel Density / Cabinet	57600	57600
IP Rating	Back IP54 / Front IP67	Back IP54 / Front IP67
Others Specifications		
Driving IC Type	Ordinary	PWM
Refrate Quality 2	Standart Quality	High Refresh
No Waterless Ripple of Camera	>%50	>%75
Driving Method " Scan "	1/10	1/10
Resolution/SQM	250 x 250	250 x 250
Pixel Density / m2	62500	62500
White Color Calibration (Adj.)	3.500K~8.500K	3.500K~8.500K
Horizontal Viewing Angle	140 (±30)	140 (±30)
Vertical Viewing Angle	140 (±30)	140 (±30)
Low Latency	Optional	Optional
HDR	Optional	Optional
Mapping	Optional	Optional
Rotation per 90 Degree	Optional	Optional
Free Rotation (with R5)	Optional	Optional
Clear View	Optional	Optional
Refresh Quality	Standart Quality	High Quality
High Refresh (PLL inside)	-	-
High Refresh Power Saving	-	!
High Refresh Dynamic Power Saving	-	-
Expected LED Lifetime %50	>100,000 Hours	>100,000 Hours
Operating Temperature Range	-15 ~ +45 (±10)	-15 ~ +45 (±10)
Operating Humidity Range	-40" # +60" ,10%-90%RH	-40" # +60" ,10%-90%RH
Power on Time (<w/sqm)	900	900
Power Consumption (<w/sqm)	780	780
Average Power Consumption (<w/sqm)	312	312
Voltage Range	47 ~ 63Hz / 110 ~ 240 VAC	47 ~ 63Hz / 110 ~ 240 VAC
Version	REV22	REV22
Packing include	Plate-Power-Cat5 Cable	Plate-Power-Cat5 Cable
Usage Area	Small Pixel Advertisement, Shopping Center & Totem	Small Pixel Advertisement, Shopping Center & Totem
Certificate	CE/EMC/LVD-ATR-EUR1 ISO-9001:2015 ISO-14001:2015	CE/EMC/LVD-ATR-EUR1 ISO-9001:2015 ISO-14001:2015

CABINET SIZE

06

size : 960mm

size : 105mm



size : 960mm

25KG.





4 IN 1 - 139KG.

size : 1.150mm

QUALITY IN DETAIL





CASE



HANDLE



LOCK



BALL



POWER



The support structure has to be provided and installed by the customer because they vary from project to project. The following issues must be considered:




Weight tolerances: Ensure that the support structure and the floor on which or the wall against which the support structure has to be installed, is qualified to handle the complete weight of the LED display screen.(which can be provided by manufacturer.

Environmental conditions: Humidity, wind, temperatures, rain, snow etc.

Ground stability

Front clearances: For making sure there is sufficient free area in front of the LED display screen and respect the maximum viewing angles and distance. Local regulations regarding such installation.







FLY BAR

960mm



CASE



POWER



SIGNAL





AVA LED

www.avaledscreen.com
info@avaledscreen.com

AVA GROUP GMBH

Adress: Goethestraße 7D - 40237 Düsseldorf / Germany

Phone : +49 211 730 64 817

