



AT288

Library, Logistics, Military, etc.

Series Highlights:

- 16bit RISC MPU
- Memory about 146KB (30Byte EPC data x 5,000 count store)
- RFID UHF 900MHz GEN2, ISO/IEC 18000-6C / 18000-6B (Option)
- Bluetooth Class II, v2.1 + SPP and HID with Windows PC, Tablet, Android and iPhone
- Cradle
- USB

Atid Co., Ltd.

Byuksan/GyungIn Digital Valley-II #1210, 184 Gasan Digital 2-Ro, Gumcheon-Gu, Seoul, KOREA, #153-783
Tel : +82-2-544-1436 Fax : +82-2-2113-0040 E-mail : atid@atid1.com www.atid1.com

AT288

Library, Logistics, Military, etc.



ACCESSORIES



Adaptor
AC Cable



Handstrap



USB Cable



Cradle

SPECIFICATION

Performance Characteristics

Processor	16bit RISC MPU
Memory	about 146KB (30byte EPC data x 5,000 count store)
Display	LED indicator
Weight	180g (with battery)
Operating Temp.	-20℃ ~ 60℃
Storage Temp.	-30℃ ~ 70℃
Humidity	95% non-condensing
Drop Spec.	1.5M Drop to concrete
Dust & Water Proof	IP65

Physical Characteristics

Audio	Buzzer (Integrated)
Standard I/O Port	Bluetooth, USB Client
Notification	LED, Buzzer
Dimensions (L x W x H)	105.6 x 53.5 (61) x 23.2 (60.3)mm

Battery Supply

Main Battery	Lithium-Ion Polymer 3.7V 2,260mAh (Rechargeable)
Power Adapter	Input AC110V ~ 240V / Output DC 5V 2A

Network Characteristics

Bluetooth	Class II, v2.1 + SPP and HID with Windows PC, Tablet, Android and iPhone
-----------	---

UHF 900 Mhz Reader

Frequency	860MHz~960MHz
Reading range	0M ~ 5M (According to Tag & Environment)
Writing range	0M ~ 3M (According to Tag & Environment)
RF output	1W EIRP
Protocol	GEN2, ISO/IEC 18000-6C, 18000-6B*
Special function	Anti-Collision

Cradle

Standard Interface	USB Client / DC Power Jack / Extra Battery Charger
--------------------	---



* All Features and specifications described are subject to change without notice.