



1. Advantages



Top Class Materials

CNC aluminum, PC+ABS (SABIC) body offer excellent strength + heat dissipation + electromagnetic shielding features. Soft material around the handle offers a comfortable grip.



Bluetooth 5.0

Supports Bluetooth 5.0, faster transmission speed and longer connection distance.



Super stable fixed design of external equipment

The design of ultra-high stability mechanical knob is adopted to break the routine and ensure the high reliability of external equipment fixation.



Outstanding Industrial Design

The appearance is compact, elegant and balanced, which makes the product eye-catching and impressive.



Excellent Mechanical Protection

Safety drop height 1.6m. With IP64 protection grade to resist dusts and splashes effectively.



Industrial-grade components + super long life cycle

Industrial-grade and military-grade components ensure stable operation in harsh environments. Over ten years of supply can be offered, which provides guarantee for the long term projects.







Ultra Long Operating Time

Pistol style hot-swappable battery system makes backup battery more convenient to be restored, so that the operating time is unlimited. (extra batteries are available)

2. Product View



3. Electrical Parameters

Mechanical parameters		Data Collections	
Materials	CNC aluminum, PC + ABS (SABIC)	Engine	Motorola EM1350
Dimensions	162*138*78mm	Support	UPC/EA Symbol SE955N/Code128/ Code39/Code93/Code11/ Interleaved 2 of 5/ Discrete 2 of 5/ Chinese 2 of 5/Codabar/MSI/ RSS.etc.
Weight	520g (battery included/standard version)	Engine	Zebra SE4750, NLS EM3396, EM3296
System Characteristics		Support	Data matrix / QR Code / PDF417 / US Planet / UK Postal, etc.
Hotswapping Battery	Pistol style hotswapping battery system	Buzzer	Indy R2000 chip
Buttons		Protocol	Ø 12*9.5mm / 2300±300Hz EPC Global UHF Class 1 Gen 2 / ISO 18000-6C / ISO 18000-6B
Power	3 ALPS buttons/ Operating force 2.5N / Operating life 1 million cycles	Frequency	902-928MHz , 865- 868MHz Optional ✓
Scan Trigger	OMRON button / Operating force 1.27N/ Operating life 10 million cycles	Output Power	0-33dBm
Power	6.000mAh chargeable li-polymer battery	Peak Inventory Speed	> 500 tags /s
USB Interface	USB TYPE C/Operating life 10,000 cycles	UHF Antenna	4dBi air medium antenna
Audio	Large speaker stereo system	Read Distance	> 10m
Charge Indicator	Bicolor LED	Supported Regions	US, Canada and other regions following US FCC Europe and other regions following ETSI EN 302 208 China, Korea, Malaysia
Application Environment		Accessories	
Operating Temp	-20° - +60°		Battery
Storage Temp	-30° - +70°		Desktop charger
Humidity	5%RH - 95%RH (non -condensing)		Charger and Data cable
Protection Grade	IP64		Hanging Lace
Safety Drop Height	2 m / 6.56ft		
Wireless Communications			
Bluetooth	Bluetooth 5.0		