

RUT271

REDCAP 5G ROUTER



RUT271 360° VIEW

The RUT271 is a Redcap 5G router, bridging the gap between 4G and full-capacity 5G. Supporting SA architecture, this 5G router can wirelessly support up to 50 end devices and features the low latency of 5G—at affordable pricing.

The RUT271 supports Wi-Fi and is backward compatible with 4G

The RUT271 supports Wi-Fi and is backward compatible with 4G LTE Cat 4. This industrial-grade RedCap 5G router is also equipped with WAN failover, two 10/100 RJ45 ports, a compact and durable design, and numerous other brilliant features for expert professional deployment.



REDCAP 5G

Low latency, high capacity, affordable pricing

FUTURE- PROOFING

Backward compatible with 4G LTE Cat 4

WI-FI

Wireless access point with Hotspot functionality

WAN FAILOVER

Automatic switching to available backup connection

RMS MANAGEMENT SYSTEM

COMPATIBLE WITH RUT271

MANAGEMENT

ALERTS

CONFIGURATION

ACCESS

FOTA



KEY FEATURES

HA	R	D١	W	Α	R	н
----	---	----	---	---	---	---

Mobile	5G Sub-6Ghz SA 223 Mbps DL , 123 Mbps UL; 4G LTE Cat 4 – LTE 195 Mbps DL, 105 Mbps UL			
CPU	Mediatek, 580 MHz, MIPS 24KEc			
RAM	128 MB, DDR2			
Storage	16 MB, NOR Flash į 32 MB, NOR Flash			
Powering options	4-pin industrial DC power socket, 9 - 30 VDC			
SIM	1 x SIM slot (Mini SIM - 2FF), 1.8 V/3 V, external SIM holder			
Antenna connectors	2 x SMA for Mobile, 1 x RP-SMA for Wi-Fi			
Ethernet	2 x RJ45 ports, 10/100 Mbps: 1 x WAN (configurable as LAN), 1 x LAN			
Wi-Fi	IEEE 802.11b/g/n (Wi-Fi 4), Access Point (AP), Station (STA)			
Inputs/Outputs	1 x Digital Input, 0 - 6 V detected as logic low, 8 - 30 V detected as logic high, 1 x Digital Output, Open collector output, max output 30 V, 300 mA			
Status LEDs	3 x Connection type status LEDs, 5 x Connection strength LEDs, 2 x LAN status LEDs, 1 x Power LED			
Operating temperature	-40 °C to 75 °C			
Housing	Aluminum housing, plastic panels			
Dimensions (W x H x D)	83 x 25 x 74 mm			
Weight	130g			

SOFTWARE

Operating system	RutOS (OpenWrt based Linux OS)		
Mobile features	Status, SMS, USSD, Black/White list, Multiple PDN, Band management, SIM PIN code management, APN, Bridge, Passthrough		
Network features	VoIP passthrough support, Network Management, Connection monitoring, Firewall, Firewall statu page, Ports management, Network topology, Hotspot, DHCP, QoS / Smart Queue Management (SQM), DNS over HTTPS, DDNS, Network backup, Load balancing, SSHFS, VRF support		
Security	Authentication, Firewall, Attack prevention, VLAN, Mobile quota control, WEB filter, Access control		
VPN and tunneling	OpenVPN, OpenVPN Encryption, IPsec, GRE, PPTP, L2TP, ZeroTier, WireGuard, Tinc		
Monitoring and Management	WEB UI, FOTA, SSH, SMS, Call, Email, TR-069, MQTT, SNMP, JSON-RPC, RMS		
Cloud solutions	RMS, ThingWorx, Cumulocity - Cloud of Things, Azure IoT Hub		
Services	OPC UA, Modbus, Data to Server, Modbus MQTT GATEWAY, DNP3, DLMS		

FRONT VIEW

BACK VIEW



