

EIL 3 Trend

MINI INSTANTANEOUS WATER HEATERS

PRODUCT-NO.: 200142

The flexible way to freshen up

Adapted to your needs Do you want a reliable supply of hot water to your hand washbasin without wasting energy? Then choose this mini instantaneous water heater. Its direct connection to the tap and fast bare wire heating system ensure that DHW is available for you immediately.



The main features

Mini instantaneous water heater with hydraulic control for small amounts of hot water available immediately

Flexible installation thanks to undersink or oversink installation

Operation with non-pressurised tap

Special aerator for perfect flow pattern

For straightforward electrical connection to any standard socket



EIL 4 Trend

Product-No.: 200143



EIL 6 Trend

Product-No.: 200144



Type	EIL 3 Trend	EIL 4 Trend	EIL 6 Trend
Part no.	200142	200143	200144

Technical data

Rated voltage	230 V	230 V	230 V
Rated voltage 1	200 V	200 V	200 V
Rated voltage 2	220 V	220 V	220 V
Rated voltage 3	230 V	230 V	230 V
Rated voltage 4	240 V	240 V	240 V
Rated output	3,53 kW	4,4 kW	5,7 kW
Rated output 1	2,7 kW	3,3 kW	4,3 kW
Rated output 2	3,2 kW	4,0 kW	5,2 kW
Rated output 3	3,53 kW	4,4 kW	5,7 kW
Rated output 4	3,8 kW	4,8 kW	6,2 kW
Rated current	15,2 A	19,1 A	24,7 A
Rated current 1	13,3 A	16,7 A	21,6 A
Rated current 2	14,5 A	18,2 A	23,6 A
Rated current 3	15,2 A	19,1 A	24,7 A
Rated current 4	15,8 A	20 A	25,8 A
Fuse protection	16 A	20 A	25 A
Fuse protection 1	16 A	20 A	25 A
Fuse protection 2	16 A	20 A	25 A
Fuse protection 3	16 A	20 A	25 A
Fuse protection 4	16 A	20 A	32 A
Frequency	50/60 Hz	50/60 Hz	50/60 Hz

Frequency 1	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 3	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 4	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Conductivity $\sigma_{15} \leq$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25\text{ }^{\circ}\text{C}$)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25\text{ }^{\circ}\text{C}$)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Resistivity $\rho_{15} \geq$	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25\text{ }^{\circ}\text{C}$)	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25\text{ }^{\circ}\text{C}$)	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$
Height	143 mm	143 mm	143 mm
Width	190 mm	190 mm	190 mm
Depth	82 mm	82 mm	82 mm
Water connection	G 3/8 A	G 3/8 A	G 3/8 A
ON	> 1,0 l/min	> 1.3 l/min	> 2.6 l/min
IP rating	IP25	IP25	IP25
Colour	white	white	white
Weight	1.40 kg	1.40 kg	1.40 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.