

# EIL 7 Premium

MINI INSTANTANEOUS WATER HEATERS

PRODUCT-NO.: 200137

**Enjoy hot water without any detours** Compact convenience that speaks for itself. Your preferred temperature without the annoyance of heat loss from the pipework along the way – this mini instantaneous water heater brings you the "new normal". The appliance with electronic closed-loop control is especially well suited to hand washbasins, where it will supply you with small amounts of warm water.

## The main features

Mini instantaneous water heater with electronic closed-loop control for small amounts of hot water available immediately

Flexible installation thanks to undersink or oversink installation

Can be operated with pressure-tested or non-pressurised taps

Accurate temperature delivery up to the maximum output

Temperature limit adjustable from approx. 30 °C to 50 °C

Special aerator for perfect flow pattern



**EIL 3 Premium**

Product-No.: 200134



**EIL 4 Premium**

Product-No.: 200135



**EIL 6 Premium**

Product-No.: 200136



Type	EIL 3 Premium	EIL 4 Premium	EIL 6 Premium
Part no.	200134	200135	200136

## Technical data

Rated voltage	230 V	230 V	230 V
Rated voltage 1	200 V	200 V	200 V
Rated voltage 2	220 V	220 V	220 V
Rated output	3.53 kW	4,4 kW	5.7 kW
Rated output 1	2.7 kW	3,3 kW	4.3 kW
Rated output 2	3.2 kW	4,0 kW	5.2 kW
Rated current	15.2 A	19,1 A	24.7 A
Rated current 1	13.3 A	16,7 A	21.6 A
Rated current 2	14.5 A	18,2 A	23.6 A
Fuse protection	16 A	20 A	25 A
Fuse protection 1	16 A	20 A	25 A
Fuse protection 2	16 A	20 A	25 A
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 1	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$ )	1000 $\mu\text{S/cm}$	1000 $\mu\text{S/cm}$	1000 $\mu\text{S/cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25 \text{ }^\circ\text{C}$ )	770 $\mu\text{S/cm}$	770 $\mu\text{S/cm}$	770 $\mu\text{S/cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$ )	1000 $\Omega \text{ cm}$	1000 $\Omega \text{ cm}$	1000 $\Omega \text{ cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25 \text{ }^\circ\text{C}$ )	1300 $\Omega \text{ cm}$	1300 $\Omega \text{ cm}$	1300 $\Omega \text{ cm}$
Height	143 mm	143 mm	143 mm

Width	190 mm	190 mm	190 mm
Depth	82 mm	82 mm	82 mm
ON	>1.5 l/min	>1.8 l/min	>2.2 l/min
IP rating	IP25	IP25	IP25
Temperature setting	30 - 50 °C	30 - 50 °C	30 - 50 °C
Colour	white	white	white
Weight	1.50 kg	1.50 kg	1.50 kg
Energy efficiency class	A	A	A



Type	EIL 7 Premium
Part no.	200137

### Technical data

Rated voltage	400 V
Rated voltage 1	380 V
Rated voltage 2	400 V
Rated output	6,5 kW
Rated output 1	5,9 kW
Rated output 2	6,5 kW
Rated current	16,3 A
Rated current 1	15,5 A
Rated current 2	16,3 A
Fuse protection	20 A
Fuse protection 1	16 A
Fuse protection 2	20 A
Frequency	50/- Hz
Frequency 1	50/- Hz
Frequency 2	50/- Hz
Phases	2/PE
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$ )	1000 $\mu\text{S/cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25 \text{ }^\circ\text{C}$ )	770 $\mu\text{S/cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$ )	1000 $\Omega \text{ cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25 \text{ }^\circ\text{C}$ )	1300 $\Omega \text{ cm}$
Height	143 mm

Width	190 mm
Depth	82 mm
ON	>2.2 l/min
IP rating	IP25
Temperature setting	30 - 50 °C
Colour	white
Weight	1.50 kg
Energy efficiency class	A

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.