

KBA 5 KA automatic

WATER BOILERS

PRODUCT-NO.: 074289

All options catered for

Cold, warm or even boiling hot? However you want your water, this automatic water heater provides it without any problems. With one lever, you can fill the container quickly and conveniently; the conventional twin lever tap is used to fill a pot or cup.

Reap the benefits of a clever combination

As we offer the right solution for every requirement, our automatic water heater is also available with a classic three lever tap. In both versions, the container is made of robust plastic. Maintaining a high level of operating convenience – so that you have hot water whenever you need it.



EBK 5 K automatic
Product-No.: 074288

The main features

Cold, warm or boiling water from one draw-off point

With boiling point detection and automatic shutdown, immediate re-boiling is possible

Variable temperature adjustment

Robust plastic container

Straightforward installation thanks to standard plug

Helpful boiling point sensor and automatic OFF control

Variable temperature adjustment

With standard chrome tap



Type	EBK 5 K automatic	KBA 5 KA automatic
Part no.	074288	074289

Technical data

Connected load	2 kW	2 kW
Power supply	1/N/PE	1/N/PE
Rated voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Nominal capacity	5 l	5 l
Tap	Twin lever tap	Three lever tap
Type	non-pressurised	non-pressurised
Cylinder material	Plastic	Plastic
Colour	white	grey
Temperature selection	100 °C	100 °C
Height	295 mm	295 mm
Width	325 mm	325 mm
Depth	197 mm	197 mm
Capacity up to	5,0 l	5,0 l
Weight	2.90 kg	2.90 kg
Tap surface	plastic-coated	chrome plated

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.