



GVN STANDART PRODUCT **Customer**

HORIZONTAL LIQUID RECEIVERS **Product**

H9A.33b.45.A4.A4.F4 **Code**

Customer Code

DESIGN DATA

Capacity [Lt.]	45 Lt.
Design Pressure [PS]	33 Bar
Pneumatic Test Pressure [PT]	36 Bar
Hydraulic Test Pressure	48 Bar
Design Temperature [TS]	Min.-20C / Max.+130C
Cooler Fluid Type	HFC-CFC-HCFC
Fluid Group	2
Category	CAT III / H
Desing Calculation	EN 14276-1/EN 13445-3
Welded Joint Efficiency	0.85
Material Group (Shell / Head)	1.2
Testing Group	3b
Corrasion Allowance	0,5 mm
Ndt	10%
Packaging Size & Weight	00*00*00 & 00 Kg.
Drawed By	Ö.TÜRKER
Approved By	D.GÜL
Date	06.01.2023
Color	RAL 5009

MATERIAL DATA

No	Connection	Model	Code	Qty
1	Inlet Connection	ROT.1 3/4" H:32	106.060.A04.001.T32	1
2	Outlet Connection	ROT.1 3/4" H:32	106.060.A04.001.T32	1
3	Safety Valve Conn.	NPT 1/2" H:18	106.060.F04.NPT.T18	1
4	Blind Plug	NPT 1/2" Plug	106.130.F04.KTP.023	1
5	Shell	Ø323,9x4 H:420	204.H09.33B.045.001	1
6	Pipe	Ø28,5x1,5 H:314	104.028.015.000.314	1
7	Head - Torispheric	Ø324x4 H:105	101.045.324.001.000	2
8	Foot	400x50x50,6 t:3	105.002.324.001.001	2

GENERAL NOTES

- Max. allowable operating pressure [PS] according to the temperature range;
- 1) Allowable operating temperature : min. -20C° / max. +130C° PS1 = 33 Bar
- 2) Allowable operating temperature : min. -40C° / max. -20C° PS2 = 24 Bar
- Unless otherwise specified dimensions in MM
- Unless otherwise specified do not scale
- Unless otherwise specified tube must be clean&free from burrs inside&outside&uitable for soldering
- Unless otherwise specified do not scale indicated thickness are min. after forming or machining
- Unless otherwise specified dimension tolerances according to EN 113445-4

REVISIONS

No	Details Of Change	Date	By
01	Bombe kalınlıkları revize olduğu için gövde boyu yeniden ayarlandı.	31.12.2024	Ö.T.
02			
03			

RELATED DRAWINGS

No	Description	Drawing No
01		
02		

