



Click the QR code for details.
Detaylar için QR koduna tıklayın.

Pressure Sensors

Basınç Sensörleri

YCQB

Order No	Model	Connection Type	Pressure Range [bar]	Max Working Pressure [bar]	Electrical Connection	Accuracy	Medium Temp. [°C]	Pack [qty]
Output signal = 0.5 to 3.5V								
10185004702	YCQB02H01	Solder ¼"	0-20	52,5	2m wires +XHP	±2% FS	-30 / 120	50
10185001502	YCQB02H01-01	Solder ¼"	0-20	52,5	2m wires +XHP	±0,8% FS	-40 / 120	50
10185015402	YCQB02H18-1	Solder ¼"	0-20	52,5	4.9m wires +XHP	±0,8% FS	-40 / 120	50
10185087602	YCQB02H165	Solder ¼"	-1-20	52,5	Packard	±0,8% FS	-40 / 120	50
10185087002	YCQB02H166	Solder 6mm	-1-20	52,5	Packard	±0,8% FS	-40 / 120	50
10185046602	YCQB03H05	Solder ¼"	0-30	75	2m wires +XHP	±0,8% FS	-40 / 120	50
10185004802	YCQB05H01	Solder ¼"	0-50	75	2m wires +XHP	±2% FS	-30 / 120	50
10185015502	YCQB02L12-1	Flare 7/16-20UNF-2B	0-20	52,5	2m wires +XHP	±0,8% FS	-40 / 120	50
10185015602	YCQB02L28-1		0-20	52,5	4.9m wires +XHP	±0,8% FS	-40 / 120	50
10185060402	YCQB02L171		-1-20	52,5	Packard	±0,8% FS	-40 / 120	50
10185046302	YCQB03L156		0-30	75	Packard	±0,8% FS	-40 / 120	50
10185067202	YCQB06L01		0-60	90	Packard	±1.5% FS	-40 / 120	50
10185044102	YCQB09L02	G1/4	0-90	225	2m wires +XHP	±2% FS	-30/+85	50



Order No	Model	Connection Type	Pressure Range [bar]	Max Working Pressure [bar]	Electrical Connection	Accuracy	Medium Temp. [°C]	Pack [qty]
Output signal = 0.5 to 4.5V								
1018 5004502	YCQB02H50	Solder ¼"	0-13.8	52,5	Packard	±2% FS	-30 / 120	
10185004602	YCQB04H50	Solder ¼"	0-34.5	75	Packard	±2% FS	-30 / 120	
10185046502	YCQB03H06	Solder ¼"	0-30	75	2m wires +XHP	±0,8% FS	-40 / 120	
10185046102	YCQB05H11	Solder ¼"	0-50	75	2m wires +XHP	±2% FS	-40 / 150	
10185004902	YCQB02L01	Flare 7/16-20 UNF-2B	0-20	52,5	2m wires +XHP	±2% FS	-30 / 120	
10185001402	YCQB02L01-01		0-20	52,5	2m wires +XHP	±0,8% FS	-40 / 120	
10185046402	YCQB03L18		0-30	75	2m wires +XHP	±0,8% FS	-40 / 120	
10185007002	YCQB05L01		0-46	75	2m wires +XHP	±2% FS	-30 / 120	
10185046002	YCQB05L63		0-50	75	2m wires +XHP	±2% FS	-40 / 150	
10185015702	YCQB01L50		-1 -9.3	52,5	Packard	±2% FS	-30 / 130	
10185004002	YCQB02L50		0-13.8	52,5	Packard	±1% FS	-30 / 120	
10185014102	YCQB02L51		0-17.2	52,5	Packard	±1% FS	-30 / 120	
10185046202	YCQB03L157		0-30	75	Packard	±0,8% FS	-40 / 120	
10185004202	YCQB04L50		0-34.5	52,5	Packard	±1% FS	S-30 / 120	
10185004302	YCQB05L50		0-46	75	Packard	±1% FS	S-30 / 120	
10185013402	YCQB05L53		0-45	75	Packard	±2% FS	-30 / 130	
10185045902	YCQB05L161		0-50	75	Packard	±2% FS	-40 / 150	
10185009102	YCQB02L100		0-20	52,5	Molex	±2% FS	-30 / 120	
10185009202	YCQB05L100		0-46	75	Molex	±1% FS	-30 / 120	

Order No	Model	Connection Type	Pressure Range [bar]	Max Working Pressure [bar]	Electrical Connection	Output signal [VDC]	Medium Temp. [°C]	Pack [qty]
High pressure use - G ¼								
10185067202	YCQB06L01*	Flare 7/16-20UNF-2B	0-60	180	Packard	0.5 to 3.5	-40/+80	
10185044102	YCQB09L02*	G 1/4	0-90	180	XHP	0.5 to 3.5	-30/+85	
10185030302	YCQB15L01	G 1/4	0-150	225	XHP	0.5 to 4.5	-30/+85	