



### Oil Pressure Valves | Yağ Basınç Valfleri

OLAB

| Order No | Model           | Pressure Setting (barg) | Kv Factor [m³/h] | PS [bar] | TS [°C]    | Inlet Connection | Outlet Connection |
|----------|-----------------|-------------------------|------------------|----------|------------|------------------|-------------------|
| S1       | 33002-FM-02-D-2 | 1,5 Fixed               | 1,5              | 45       | -40 / +150 | 3/8" SAE Female  | 3/8" SAE Male     |
| S2       | 33003-FM-02-D-2 | 3,0 Fixed               |                  |          |            |                  |                   |



### Oil Pressure Valves | Yağ Basınç Valfleri

CASTEL

| Order No | Model     | Pressure Setting (barg) | Kv Factor [m³/h] | PS [bar] | TS [°C]    | Inlet Connection | Outlet Connection |
|----------|-----------|-------------------------|------------------|----------|------------|------------------|-------------------|
| S02      | 3150W/X02 | 1,4 Fixed               | 1,6              | 80       | -40 / +150 | 3/8" SAE Female  | 3/8" SAE Male     |
| S03      | 3150W/X03 | 3,0 Fixed               |                  |          |            |                  |                   |

### Safety Valves | Emniyet Ventilleri

OLAB

| Order No | Code             | Inlet Male [NPT] | Outlet Male [SAE] | Orifice Ø [mm] | Discharge Coefficient | PS [bar] | TS [°C]    | Set Press. Range | Over Pressure       | Blowdown            |
|----------|------------------|------------------|-------------------|----------------|-----------------------|----------|------------|------------------|---------------------|---------------------|
| G1       | 40070-K2N2-0-280 | 1/4"             | 3/8"              | 7              | 0,6                   | 28       | -50 / +150 | 28 / 45 bar      | 10% of set pressure | 10% of set pressure |
| G2       | 40070-K3N2-0-280 | 3/8"             | 3/8"              | 7              | 0,6                   | 28       |            |                  |                     |                     |
| G3       | 40095-K4N4-0-280 | 1/2"             | 5/8"              | 9,5            | 0,45                  | 28       |            |                  |                     |                     |
| G5       | 40095-K4N4-0-300 | 1/2"             | 5/8"              | 9,5            | 0,45                  | 30       |            |                  |                     |                     |
| G6       | 40095-K4N4-0-450 | 1/2"             | 5/8"              | 9,5            | 0,45                  | 45       |            |                  |                     |                     |



### Safety Valves | Emniyet Ventilleri

CASTEL

| Order No | Code        | Inlet Male [NPT] | Outlet Male [SAE] | Orifice Ø [mm] | Discharge Coefficient | PS [bar] | TS [°C]    | Set Press. Range | Over Pressure       | Blowdown            |
|----------|-------------|------------------|-------------------|----------------|-----------------------|----------|------------|------------------|---------------------|---------------------|
| G28      | 3060/45C-28 | 1/2"             | 5/8"              | 9,5            | 0,45                  | 28       | -50 / +120 | 9 / 50 bar       | 10% of set pressure | 10% of set pressure |
| G30      | 3060/45C-30 | 1/2"             | 5/8"              | 9,5            | 0,45                  | 30       |            |                  |                     |                     |
| G45      | 3060/45C-45 | 1/2"             | 5/8"              | 9,5            | 0,45                  | 45       |            |                  |                     |                     |



### Shut-Off Valve For Safety Valves | Emniyet Ventili İçin Kapama Vanası

| Order No | Code                | Inlet Male [NPT] | Outlet Male [SAE] | DN Ø [mm] | PS [bar] |
|----------|---------------------|------------------|-------------------|-----------|----------|
| G50      | 37000-FM-03-03-13-2 | 1/2"             | 1/2"              | 13        | 80       |



### Changeover Valves | Değişim Vanaları

| Order No | Code    | Inlet Male [NPT] | Outlet Female [NPT] | Orifice Ø [mm] | PS [bar] | TS [°C]    | Over Pressure       | Blowdown            |
|----------|---------|------------------|---------------------|----------------|----------|------------|---------------------|---------------------|
| G22      | 3032/44 | 1/2"             | 1/2"                | 13             | 80       | -35 / +105 | 10% of set pressure | 10% of set pressure |



### Air Conditioner Brackets | Klima Montaj Konsolları

| Type                        | Model       | BTU         | L [mm] | L1 [mm] | L2 [mm] | L3 [mm] | Thickness [T] | Slot [S1] | Slot [S2] |
|-----------------------------|-------------|-------------|--------|---------|---------|---------|---------------|-----------|-----------|
| Welded type<br>Kaynaklı tip | ACB.W01.400 | 9000-12000  | 395    | 396     | 55      | 50      | 2             | Ø8x95     | Ø10x25    |
|                             | ACB.W01.500 | 18000-24000 | 490    | 492     | 65      | 60      | 2             | Ø8x95     | Ø10x25    |
|                             | ACB.W01.600 | 30000-60000 | 566    | 568     | 65      | 60      | 2             | Ø8x130    | Ø10x25    |
|                             | ACB.W01.700 | -           | 595    | 691     | 93      | 70      | 2             | Ø10x130   | Ø10x25    |
| Screw type<br>Vidalı tip    | ACB.S01.400 | 9000-12000  | 395    | 396     | 55      | 50      | 2             | Ø8x95     | Ø10x25    |
|                             | ACB.S01.500 | 18000-24000 | 490    | 492     | 65      | 60      | 2             | Ø8x95     | Ø10x25    |
|                             | ACB.S01.600 | 30000-60000 | 566    | 568     | 65      | 60      | 2             | Ø8x130    | Ø10x25    |

