



TECHNICAL REQUIREMENT:

- 翅片FPI=12.7;
- 扁管规格:1.6*1.3*1.6,材料:AA3102;
- 翅片规格: 0.08*1.6, 高度: 8.1;
- FIN:0.08*1.6, FIN HEIGHT:8.1;
- 进出口管为铜管;

INLET AND OUTLET PIPES ARE COPPER TUBES;

DESIGN PRESSURE:4.5 Mpa, BURST PRESSURE:13.5 Mpa;

签字
Sign

图纸客户确认栏
Customer Approve

[Signature]

公差/Unmarked	Linear	Tolerance
±0.10	>30	±0.10
±0.15	>120	±0.15
±0.20	>180	±0.20
±0.25	>240	±0.25
±0.30	>300	±0.30
±0.40	>360	±0.40
±0.50	>420	±0.50

公差/Unmarked	Linear	Tolerance
±0.10	>30	±0.10
±0.15	>120	±0.15
±0.20	>180	±0.20
±0.25	>240	±0.25
±0.30	>300	±0.30
±0.40	>360	±0.40
±0.50	>420	±0.50

设计/DRN	changchun1	批准/APP	日期/Date	2015.10.10
校对/CHK	李强	审核/ENG	日期/Date	2015.10.10
工艺/MFG				

Sanhua (Hangzhou) Micro Channel Heat Exchanger Co., LTD

SMH PK: 12950001

设计/DRN	changchun1	批准/APP	日期/Date	2015.10.10
校对/CHK	李强	审核/ENG	日期/Date	2015.10.10
工艺/MFG				

更改文件号/内容

签字/Sign

日期/Date