



TECHNICAL REQUIREMENT:

- 1.翅片FPI=12.7;  
FPI=12.7;
- 2.扁管规格:16\*1.3\*16,材料:AA3102;  
TUBE:16\*1.3\*16, Material: AA3102;
- 3.翅片规格: 0.08\*16, 高度: 8.1;  
FIN:0.08\*16, FIN HEIGHT:8.1;
- 4.进出口管为铜管;
- 5.设计压力: 4.5MPa, 爆破压力: 13.5MPa;  
DESIGN PRESSURE:4.5 Mpa, BURST PRESSURE:13.5 Mpa;

回路示意图

回路示意图	
IN	10
	8
	6
OUT	4

公差/Unmarked Linear Tolerance	公差/Unmarked Angle Tolerance
≤0.1	±0.5°
>0.30	±1.0°
>0.120	±1.5°
>120.300	±2.0°
>1000.2000	±3.0°
>2000	±4.0°
>5000	±5.0°

未注线性尺寸公差/Unmarked Linear Tolerance	公差/Unmarked Angle Tolerance	比例/Scale	版本/Rev.	页码/Page
≤0.1	±0.5°	1:4	00	1
>0.30	±1.0°	1:4	00	1
>0.120	±1.5°	1:4	00	1
>120.300	±2.0°	1:4	00	1
>1000.2000	±3.0°	1:4	00	1
>2000	±4.0°	1:4	00	1
>5000	±5.0°	1:4	00	1

图纸客户确认栏  
Customer Approve

签字  
Sign

Sanhua (Shanghai) Micro Channel Heat Exchanger Co., LTD

1:4

00

1

X001-EU07

12950007

更改文件号/内容	签字/Sign	日期/Date