



- TECHNICAL REQUIREMENT:**
- 1.FPI=23;
 - 2.INLET AND OUTLET PIPES ARE COPPER TUBES;
 - 3.TUBE:25.4*1.3*26;
 - 4.INTERNAL VOLUME 1.634L;
 - 5.MAX OPERATING PRESSURE 4.5MPA ;
 - 6.BURST PRESSURE :13.5MPA.

未注线性尺寸公差/Unmarked Linear Tolerance						
≤6	>6~30	>30~120	>120~400	>400~1000	>1000~2000	>2000
±0.5	±1	±1.5	±2	±3	±4	±5
未注角度公差/Unmarked Angle Tolerance						
直角/Right Angle	±2°		其它角/Other Angle	±3°		
设计/DRN	Tianmin Si		标准化/STD			
校对/CHK			审定/APV			
审核/ENG			批准/APP			
工艺/MFG						

图纸客户确认栏	
Customer Approve	
签字	Sign
SanHua(HangZhou) Micro Channel Heat Exchanger Co.,LTD	
X001-SD17-5	
SMH PN:101005500	

一角法	1ST ANGLE PROJ
比例	1:6
版本	00
Rev.	

005500101-Nd HWS
5-LTDS-T00X

标记	数量	版本	更改文件号/内容	签字	日期
Mark	QTY.	Rev	Revision No./Details	Sign.	Date