
Any unauthorized use of this drawing, any copying or passing on to third parties requires the explicit approval of ebm Werke. Any violations of this will be prosecuted in Civil and Penal Court.

CAD: CAD0055463
DISTRIBUTION: V-PG2



ebmpapst
ebm-papst Mulfingen GmbH & Co. KG

Delivery Specification

No. 10549


Unit: axial fan with guard grille
Type: S4E350-AQ02-86
Motor: single phase motor with capacitor
Customer:
Motor Type: M4E074-EI..-..
Customer-type:

Type	voltage V	frequency Hz	power consumption W	power output W	current consumption A	air volume m³/h	static pressure Pa	speed min⁻¹			noise level dBA	capacitor µF	capacitor VDB
S4E350-AQ02-86	230	50	145		0,68	3450	0	1450			63	5	400
	230	60	205		0,9	4020	0	1700			67	5	400

Winding layout No.: 1788 Resistance: 39,5/59Ω
Insulation class: F
Operating type: S1
Permissible ambient temperature: 85/75°C
△t= 55/65K at 255V + max. 100Pa
Motor protection: thermocontact
Data plate: label
Type: S4E350-AQ02-86
230 V 50/60 Hz 145/205W 0,68/0,9 A 1450/1700 min⁻¹ 5 µF 400 VDB
High-voltage test according to EN 60335-1 with 2000V ④
Electrical connection: lead wire silicon 4G, length 1000mm from stator, 85mm dismantelt.

Material/surface treatment: rotor with condensation drainholes varnished black, stator moisture protected, guard grille plastic coated.

Bearings: ball bearings
Direction of rotation: anticlockwise
Looking at rotor side:
Airflow direction: "V"
Balancing grade: fan balanced dynamically in two planes
Protection class: IP44 in accordance with EN 60034-5
Mounting position: optional
Approx. weight per unit: kg
Wiring diagrams:



3	48214	21.07.03	JO																						
2	48125	09.07.03	JO																						
1	47868	05.06.03	JO			5	52716	03.02.05	JO																
–	–	20.05.03	JO			4	48949	23.10.03	JO																

AutoCAD