



Model	Product Image	Product Name	Operating Mode	Product Parameter Specifications	Protection Level	Charging time	Discharge time	Battery Working Temperature	Luminous flux	Beam Angle	Recommended installation height	Irradiation Area
SL200W		Starlight 200W	Lighting Control+Remote Control+Rader	Solar panel: 5V 7W Solar panel size: 172*291 MM Lithium battery: 3.2V 5000 MAH LED bead: Epistar528LED - 132LED*4pcs Lamp material: ABS Lamp size: 40*21*5 CM Tube diameter: 70 MM	IP66	5-6 H	More than 12 hours	-10°C ~ 60 °C	2000LM	120°	3-4m	80-120 m2
SL250W		Starlight 250W	Lighting Control+Remote Control+Rader	Solar panel: 5V 9W Solar panel size: 193*383 MM Lithium battery: 3.2V 10000 MAH LED bead: Epistar660LED - 132LED*5 pcs Lamp material: ABS Lamp size: 50*24*6 CM Tube diameter: 70 MM	IP66	5-6 H	More than 12 hours	-10°C ~ 60 °C	2500LM	120°	4-5m	80-120 m2
SL300W		Starlight 300W	Lighting Control+Remote Control+Rader	Solar panel: 5V 15W Solar panel size: 208*578 MM Lithium battery: 3.2V 15000 MAH LED bead: Epistar924LED - 132LED*6pcs Lamp material: ABS Lamp size: 75*25*70 MM Tube diameter: 70 MM	IP66	5-6 H	More than 12 hours	-10°C ~ 60 °C	3000LM	120°	4-6m	100-150 m2